



Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Outdoor, Retail
Specification	Performance

Luppa

Luppa CCT Multi Wattage Black Self-Test Emergency
Code: ALUP/1/B/SM3



PRODUCT FEATURES

- IP66 rated die-cast aluminium wall light with opal polycarbonate diffuser suitable for education, commercial and industrial applications
- Integrated switch on the LED board allows for the section behind the eyelid to be deactivated, improving energy efficiency when using the eyelid trim
- Tamper-proof stainless steel allen key screws
- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 2 outputs, in one luminaire
- Gear tray located on the diffuser, allowing the base to be installed and then the diffuser connected, this coupled with removeable conduit entries on base ensure a quick and simple installation
- Non-dimmable

GENERAL INFORMATION

Wattage	16W - 23W
Lumens Delivered	2100lm - 3200lm (4000K)
Lm/W	135lm/W - 140lm/W (4000K)
Beam Angle	107
CRI	80
CCT	3000/4000K
Input	220-240V
Operating Temp	5C to 40°C
SDCM	5
UGR	25
Product Weight without Packaging	2.3 kg

TECHNICAL INFORMATION

Light Source	LED
Colour / Finish	Black
IP Rating	IP66
IK Rating	IK08
Class Protection	1
Internal / External	Internal / External
Surface / Recessed / Suspended	Ceiling, Surface, Wall
Lumen Depreciation	L80 72,000h
Warranty (Years)	5
CE Mark	Yes
Diameter	298 mm



Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Outdoor, Retail
Specification	Performance

Luppa

Luppa CCT Multi Wattage Black Self-Test Emergency

Code: ALUP/1/B/SM3

