pollock Lifts

Classic 1m Steplift

A cost-effective lift with up to one metre of travel



A reliable, cost-effective steplift

Classic 1m Steplift

The new Classic 1metre Steplift boasts a smaller footprint along with an increased load capacity - now capable of lifting 280kg to a maximum of 1m between two floors.

With increased clear access, the hydraulically driven, scissor based platform is suitable for both internal and external environments. Functional yet stylish, our Classic 1m Steplift moves quietly between levels to provide safe and reliable access in public buildings and in the home. Further key features include an on-board drive and powered upper and lower gates combined with the fixed ramp (no pit).

New model | **Battery operation**

Smaller footprint | **Higher carrying capacity**

Features

- Pump unit is integrated within the lift offering reduced vandalism risk
- No need for separate control unit or pump location
- Easy access to pump for servicing
- Easier and faster to install
- Simpler to use
- More compact
- New stylish protective bellows - more rigid/durable
- Improved IP 67 rated switching (waterproof) with easy service access
- Easy to use emergency lowering system
- 1 day installation - minimal builders work
- Can be relocated
- Low maintenance
- Aluminium checker plate flooring

Sectors

- Public Access
- At Home

Platform Sizes

- 800 x 1400mm
- 900 x 1400mm
- 1100 x 1400mm

Options

Gate

- Manual Lower Gate
- On board ramp

Controls

- Autodialler
- Alarm
- Keyswitch
- Keyswitch isolation
- Remote controls
- Full ambulant user controls
- Full controls at serviced floors
- Remote call posts

Finish


- Handrails
- Silicon acrylic infill panels
- Aluminium infill panels

Custom colour

Configurations

All measurements are in millimetres (mm)


Through Entry



Internal Dims	External Dims	
Models	Ramp[1]/No Upper	Ramp & Upper
800*1400	980 x 1700	980 x 1810
900*1400	1080 x 1700	1080 x 1810
1100*1400	1280 x 1700	1280 x 1810


[1] Ramp can be on board, or fixed at the lower level. Fixed is 15mm shorter.

Bridging Steps



Models	Internal Dims	External Dims
800+1 Step	800 x 1400	980 x 1990
800+2 Steps	980 x 2240	980 x 2240
800+3 Steps	980 x 2490	980 x 2490

Pit Mounted



Internal Dims	External Dims	
Models	Lower/No Upper	Lower & Upper
800*1400	980 x 1445	980 x 1555
900*1400	1080 x 1445	1080 x 1555
1100*1400	1280 x 1445	1280 x 1555

An integrated ramp can be fitted.

Note: Specifications are correct at time of print and is subject to change as part of our ongoing Research and Development programme.

Technical Specifications

Location	Internal or External environments
Usage	Public or domestic use by ambulant and wheelchair users (handrails required)
Maximum passengers	Wheelchair user plus attendant (lower gate required)
Lift Safe Working Load	280kg
Platform Sizes (w) x (l)	800 x 1400mm | 900 x 1400mm | 1100 x 1400mm
Design & Manufacturing Standard	BS 6440:2011; EN 81-41(ref. only) Machinery Directive 2006/42/EC

The comprehensive ranges from Pollock Lifts . . .

	Public Access	At Home	Service & Goods
1m Steplift Classic	✓	✓	
1m Steplift Executive	✓	✓	
Independence Steplift 2m/3m	✓	✓	
Incline Platform Lift	✓	✓	
Passenger Lift	✓		
Vertical Platform Lift	✓		
Through Floor Lift		✓	
Residential Elevator		✓	
Residential Stair Lift		✓	
Service Lift			✓
Goods Lift			✓
Dumb Waiter			✓

Explore all our models at **pollocklifts.co.uk**

Get in touch for more information:

1 Sloefield Drive | Trooperslane Industrial Estate | Carrickfergus | Co. Antrim | BT38 8GX | N.Ireland
T 028 9336 8167 | E info@pollocklifts.co.uk | www.pollocklifts.co.uk