

REMOVE EXISTING VENTILATOR AND BRICKWORK TO EXISTING WALKIN AND EXTERIOR CRACKS VERTICALLY TO FLOOR LEVEL MAKE GOOD ALL SURFACES

OPEN LATTICE SKILL LAMPILS BEATED TO WALL AND ON 4 AND 11RS COLUMNS BEATED TO FRACK AND LAMPILS

FROM LATTICE CELL WALLS
BOILED TO WALK AND ON
4 AND 1HS COLUMNIS BOILED TO
FLOCK AND WALLS

250 ml
60%
1

~~220 Max~~
~~Rise~~

HEAT CHECKER RATE
TREASORS KKK 100 MM
BETWEEN RIVER & TREAS

900 To Handball

4 NO SQUARE SECTIONAL POSTS
TO SUPPORT WALLS BOLTED
TO EXISTING CONCRETE BASE
AND BOLTED / WELDED TO
LANDING REINFORCED BEAMS

SPACES TO
LEADING &
STARS. MAX
100mm SPACES
BETWEEN!

MAKE UP GRADU
F. REQUIRED 7

MAXIMUM 16 THREADS ABOUT 4000
MINIMUM 15 FIBERS OVERALL HEIGHT 3300

RAKEMOOD MILL • NEW ACCESS STAIRS TO FORMER DRYING ROOM

check all dimensions on site prior to fabrication