Declaration of Performance

Category 10 comprising of
Pre War Banded Wirecut
Reclamation Banded Wirecut
Weathered Banded Wirecut

Cat 10 - BW - 2015

Group HD, Category II Handmade Clay Bricks

Intended use or uses of the contruction product, in accordance with applicable harmonised technical specification, as forseen by the manufacturer
Facing clay masonary unit for internal or external use, load bearing or non load bearing masonary structures

Essential Characteristics	Performance		Harmonised Technical Specification
Dimensional Tolerances mm	228 x 108 x 73 228 x 108 x 65		BS EN 771-1 2011
	Tolerance	T1	
	Range	R2	
Compressive Strength (Standard shape, tested normal to the bed face of the unit) N/mm^2	Mean	40	
	Category	II	
Dimensional Stability N/mm^2	NPD		
Bond Strength Fixed value N/mm2	NPD		
Active Soluble Salts	S2		Commision Decision 2000/605/EC
Reaction to Fire	A1		BS EN 771-1 2011
Water Absorption %	14		
Water Vapour Permeability	NPD		
Direct Airborne Sound Insulation kg/m^2 (gross)	NPD		
Thermal Properties	NPD		
Durability Against Freeze Thaw	F2		
Dangerous Substances	NPD		

The performance of the product(s) identified above is in conformity with the declared values

Signed for and on behalf of the manufacturer by:

Dean Royle - Managing Director

Manchester Brick Specialists Ltd
Unit 15B Orchard Trading Estate
Orchard Street
Salford
M6 6FL

Sedex