

Land at Parkfield House, Manchester Old Road, Middleton

Air Quality Assessment

March 2023

Report Issue

Report Title: Air Quality Assessment - Old Manchester Road, Middleton

Report Reference: 6290

Field	Report Version			
	1	2	3	4
Prepared by	Alec Barnett	Alec Barnett		
Position	Air Quality Consultant	Air Quality Consultant		
Reviewed by	Emily Pears-Ryding	Emily Pears-Ryding		
Position	Principal Air Quality Consultant	Principal Air Quality Consultant		
Authorised by	Jethro Redmore	Jethro Redmore		
Position	Director	Director		
Date of Issue	20 th January 2023	8 th March 2023		
Comment	-	-		

Taylor Road, Urmston, Manchester, M41 7JQ

info@red-env.co.uk | 0161 706 0075 | www.red-env.co.uk

This report has been prepared by Redmore Environmental Ltd in accordance with the agreed terms and conditions of appointment. Redmore Environmental Ltd cannot accept any responsibility for any use of or reliance on the contents of this report by any third party.

Executive Summary

Redmore Environmental Ltd was commissioned by Muller Property Group to undertake an Air Quality Assessment in support of a mixed-use development on land off Old Manchester Road, Middleton.

The proposals comprise demolition of the existing structures and subsequent construction of a care home to provide 80 units alongside 20 residential dwellings, associated car parking and infrastructure.

The development may lead to the exposure of future occupants to any existing air quality issues at the site, as well as adverse impacts at sensitive locations during the construction and operational phases. As such, an Air Quality Assessment was undertaken in order to determine baseline conditions, consider location suitability for the proposed end-use and assess potential effects associated with the scheme.

Potential construction phase air quality impacts from fugitive dust emissions were assessed as a result of demolition, earthworks, construction and trackout activities. It is considered that the use of good practice control measures would provide suitable mitigation for a development of this size and nature and reduce potential impacts to an acceptable level.

During the operational phase of the development there is the potential for the exposure of future occupants to elevated pollution levels. Dispersion modelling was therefore undertaken in order to predict concentrations across the proposed site as a result of emissions from the highway network. Results were subsequently verified using local monitoring data.

The results of the dispersion modelling assessment indicated that predicted pollutant levels were below the relevant criteria across the development. As such, the site is considered suitable for the proposed end use from an air quality perspective and mitigation is not required.

During the operational phase of the development there is also the potential for air quality impacts as a result of traffic exhaust emissions associated with vehicles travelling to and from the site. These were assessed using standard screening criteria. Due to the limited number of anticipated vehicle trips associated with the proposals, road traffic exhaust impacts were not predicted to be significant.

Based on the assessment results, air quality factors are not considered a constraint to planning consent for the development.

Table of Contents

1.0	INTRODUCTION	1
1.1	Background	1
1.2	Site Location and Context	1
2.0	LEGISLATION AND POLICY	2
2.1	Legislation	2
2.2	Local Air Quality Management	4
2.3	Dust	4
2.4	National Planning Policy	5
2.5	National Planning Practice Guidance	6
2.6	Local Planning Policy	7
3.0	METHODOLOGY	10
3.1	Introduction	10
3.2	Construction Phase Assessment	10
	Step 1	11
	Step 2	11
	Step 3	18
	Step 4	18
3.3	Operational Phase Assessment	18
	Potential Future Exposure	18
	Potential Development Impacts	19
4.0	BASELINE	20
4.1	Introduction	20
4.2	Local Air Quality Management	20
4.3	Air Quality Monitoring	20
4.4	Background Pollutant Concentrations	21
4.5	Sensitive Receptors	22
5.0	ASSESSMENT	25
5.1	Introduction	25
5.2	Construction Phase Assessment	25
	Step 1	25
	Step 2	25
	Step 3	28
	Step 4	31
5.3	Operational Phase Assessment	31

Potential Future Exposure	31
Potential Development Impacts	31
6.0 CONCLUSION	33
7.0 ABBREVIATIONS	35

Appendices

Appendix 1 - Assessment Input Data

Appendix 2 - Curricula Vitae

1.0 INTRODUCTION

1.1 Background

1.1.1 Redmore Environmental Ltd was commissioned by Muller Property Group to undertake an Air Quality Assessment in support of a mixed-use development on land off Old Manchester Road, Middleton.

1.1.2 The development may lead to the exposure of future occupants to any existing air quality issues at the site, as well as adverse impacts at sensitive locations during the construction and operational phases. As such, an Air Quality Assessment was undertaken in order to determine baseline conditions, consider location suitability for the proposed end-use and assess potential effects associated with the scheme.

1.2 Site Location and Context

1.2.1 The site is located on land off Old Manchester Road, Middleton, at approximate National Grid Reference (NGR): 386229, 405530. Reference should be made to Figure 1 for a map of the site and surrounding area.

1.2.2 The proposals comprise demolition of the existing structures and subsequent construction of a care home to provide 80 units alongside 20 residential dwellings, associated car parking and infrastructure.

1.2.3 The development is located in close proximity to the A576 and associated road vehicle exhaust emissions. As such, the proposals may introduce future occupants to elevated pollutant levels. An Air Quality Assessment was therefore undertaken in order to determine baseline conditions and consider location suitability for the proposed end-use. Potential impacts associated with the construction and operation of the scheme have also been assessed using standard screening methodologies. This is detailed in the following report.

2.0 LEGISLATION AND POLICY

2.1 Legislation

2.1.1 The Air Quality Standards Regulations (2010) and subsequent amendments include Air Quality Limit Values (AQLVs) for the following pollutants:

- Nitrogen dioxide (NO₂);
- Sulphur dioxide;
- Lead;
- Particulate matter with an aerodynamic diameter of less than 10µm (PM₁₀);
- Particulate matter with an aerodynamic diameter of less than 2.5µm (PM_{2.5});
- Benzene; and,
- Carbon monoxide.

2.1.2 Air Quality Target Values have also been provided for several additional pollutants. It should be noted that the AQLV for PM_{2.5} stated in the Air Quality Standards Regulations (2010) was amended in the Environment (Miscellaneous Amendments) (EU Exit) Regulations (2020).

2.1.3 The Air Quality Strategy (AQS) was produced by the Department for Environment, Food and Rural Affairs (DEFRA) and published in July 2007¹. The document contains standards, objectives and measures for improving ambient air quality, including a number of Air Quality Objectives (AQOs). These are maximum ambient pollutant concentrations that are not to be exceeded either without exception or with a permitted number of exceedences over a specified timescale. These are generally in line with the AQLVs, although the requirements for the determination of compliance vary.

2.1.4 Table 1 presents the AQOs and AQLVs for pollutants considered within this assessment.

¹ The AQS for England, Scotland, Wales and Northern Ireland, DEFRA, 2007.

Table 1 Air Quality Objectives/Air Quality Limit Values

Pollutant	Air Quality Objective/Air Quality Limit Value	
	Concentration (µg/m ³)	Averaging Period
NO ₂	40	Annual mean
	200	1-hour mean, not to be exceeded on more than 18 occasions per annum
PM ₁₀	40	Annual mean
	50	24-hour mean, not to be exceeded on more than 35 occasions per annum
PM _{2.5}	20	Annual mean

2.1.5 The Environment Act (2021) was published on 9th November 2021 and makes provision for the setting of lower PM_{2.5} targets. However, the AQLV outlined in Table 1 remains the adopted air quality standard within the UK until further legislation is implemented.

2.1.6 Table 2 summarises the advice provided in DEFRA guidance² on where the AQOs for pollutants considered within this report apply.

Table 2 Examples of Where the Air Quality Objectives Apply

Averaging Period	Objective Should Apply At	Objective Should Not Apply At
Annual mean	All locations where members of the public might be regularly exposed Building façades of residential properties, schools, hospitals, care homes etc.	Building façades of offices or other places of work where members of the public do not have regular access Hotels, unless people live there as their permanent residence Gardens of residential properties Kerbside sites (as opposed to locations at the building façade), or any other location where public exposure is expected to be short term
24-hour mean	All locations where the annual mean objective would apply, together with hotels Gardens of residential properties	Kerbside sites (as opposed to locations at the building façade), or any other location where public exposure is expected to be short term

² Local Air Quality Management Technical Guidance (TG22), DEFRA, 2022.

Averaging Period	Objective Should Apply At	Objective Should Not Apply At
1-hour mean	All locations where the annual mean and 24 and 8-hour mean objectives apply. Kerbside sites (for example, pavements of busy shopping streets) Those parts of car parks, bus stations and railway stations etc which are not fully enclosed, where members of the public might reasonably be expected to spend one hour or more Any outdoor locations where members of the public might reasonably be expected to spend one hour or longer	Kerbside sites where the public would not be expected to have regular access

2.2 **Local Air Quality Management**

2.2.1 Local Authorities (LAs) are required to periodically review and assess air quality within their area of jurisdiction under the system of Local Air Quality Management (LAQM). This review and assessment of air quality involves comparing present and likely future pollutant concentrations against the AQOs. If it is predicted that levels at locations of relevant exposure, as summarised in Table 2, are likely to be exceeded, the LA is required to declare an Air Quality Management Area (AQMA). For each AQMA the LA is required to produce an Air Quality Action Plan, the objective of which is to reduce pollutant concentrations in pursuit of the AQOs.

2.3 **Dust**

2.3.1 The main requirements with respect to dust control from industrial or trade premises not regulated under the Environmental Permitting (England and Wales) Regulations (2016) and subsequent amendments, such as construction sites, is that provided in Section 79 of Part III of the Environmental Protection Act (1990). The Act defines nuisance as:

"any dust, steam, smell or other effluvia arising on industrial, trade or business premises and being prejudicial to health or a nuisance."

2.3.2 Enforcement of the Act, in regard to nuisance, is currently under the jurisdiction of the local Environmental Health Department, whose officers are deemed to provide an independent evaluation of nuisance. If the LA is satisfied that a statutory nuisance exists, or is likely to occur or happen again, it must serve an Abatement Notice under Part III of

the Environmental Protection Act (1990). The only defence is to show that the process to which the nuisance has been attributed and its operation are being controlled according to best practicable means.

2.4 National Planning Policy

2.4.1 The revised National Planning Policy Framework³ (NPPF) was published in July 2021 and sets out the Government's planning policies for England and how these are expected to be applied.

2.4.2 The purpose of the planning system is to contribute to the achievement of sustainable development. In order to ensure this, the NPPF recognises three overarching objectives, including the following of relevance to air quality:

"c) an environmental objective - to protect and enhance our natural, built and historic environment; including making effective use of land, improving biodiversity, using natural resources prudently, minimising waste and pollution, and mitigating and adapting to climate change, including moving to a low carbon economy."

2.4.3 Chapter 15 of the NPPF details objectives in relation to conserving and enhancing the natural environment. It states that:

"Planning policies and decisions should contribute to and enhance the natural and local environment by:

[...]

e) preventing new and existing development from contributing to, being put at unacceptable risk from, or being adversely affected by, unacceptable levels of soil, air, water or noise pollution or land instability. Development should, wherever possible, help to improve local environmental conditions such as air and water quality [...]."

³ NPPF, Ministry of Housing, Communities and Local Government, 2021.

2.4.4 The NPPF specifically recognises air quality as part of delivering sustainable development and states that:

"Planning policies and decisions should sustain and contribute towards compliance with relevant limit values or national objectives for pollutants, taking into account the presence of Air Quality Management Areas and Clean Air Zones, and the cumulative impacts from individual sites in local areas. Opportunities to improve air quality or mitigate impacts should be identified, such as through traffic and travel management, and green infrastructure provision and enhancement. So far as possible these opportunities should be considered at the plan-making stage, to ensure a strategic approach and limit the need for issues to be reconsidered when determining individual applications. Planning decisions should ensure that any new development in Air Quality Management Areas and Clean Air Zones is consistent with the local air quality action plan."

2.4.5 The implications of the NPPF have been considered throughout this assessment.

2.5 National Planning Practice Guidance

2.5.1 The National Planning Practice Guidance⁴ (NPPG) web-based resource was launched by the Department for Communities and Local Government on 6th March 2014 and updated on 1st November 2019 to support the NPPF and make it more accessible. The air quality pages are summarised under the following headings:

1. What air quality considerations does planning need to address?
2. What is the role of plan-making with regard to air quality?
3. Are air quality concerns relevant to neighbourhood planning?
4. What information is available about air quality?
5. When could air quality considerations be relevant to the development management process?
6. What specific issues may need to be considered when assessing air quality impacts?
7. How detailed does an air quality assessment need to be?
8. How can an impact on air quality be mitigated?

⁴ <https://www.gov.uk/guidance/air-quality--3>.

2.5.2 These were reviewed and the relevant guidance considered as necessary throughout the undertaking of this assessment.

2.6 Local Planning Policy

2.6.1 The Rochdale Core Strategy⁵ is a key document in the Rochdale Local Plan and was adopted by Rochdale Borough Council (RBC) in October 2016. It sets out the strategic planning framework for the borough's future development needs up to 2028.

2.6.2 Review of the document indicated the following policies of relevance to the assessment:

"Policy G9 - Reducing the Impact of Pollution, Contamination and Land Instability

We will reduce all forms of pollution, contamination and land instability in the borough, by:

- a) Focusing on measures that reduce air pollution in Air Quality Management Areas, and other areas where pollution levels are unacceptable, particularly around motorways and main roads;
- b) Requiring that development does not have impacts that lead to an unacceptable increase in air, water, noise, light or other pollution;
- c) Ensuring sensitive new developments such as housing, schools and hospitals are not adversely affected by existing sources of pollution such as roads and certain types of industry;
- d) Requiring a Low Emissions Strategy where development requires a Transport Assessment, and in other circumstances as appropriate;

[...]

g) Using planning conditions or obligations to control pollution from new development, or the impact of pollution on new development."

"Policy DM1 - General Development Requirements

⁵ Rochdale Core Strategy, Adopted October 2016, RBC, 2016.

All development proposals, including changes of use of land and buildings, extensions and alterations, will be expected to demonstrate that they:

[...]

d. Mitigate against any impacts due to noise, air, dust, light and odour pollution, traffic generation or inadequate access, where such mitigation is identified as being necessary;

[...]

f. Do not have an adverse impact on health, through its impact or the effect of existing problems e.g. land contamination, or poor air quality;

[...]."

"DM2 - Delivering Planning Contributions and Infrastructure

[...]

3. All types of development

For all types of development, including housing, we will seek contributions for any infrastructure or other measures necessary to mitigate any on site or off-site impacts from the development.

These contributions may cover, dependent on need:

[...]

Mitigation or compensation against environmental impacts e.g. noise, air quality (particularly in Air Quality Management Areas);

[...]."

2.6.3 The implications of the above policies were taken into consideration throughout the assessment.

3.0 METHODOLOGY

3.1 Introduction

3.1.1 The proposed development has the potential to expose future occupants to elevated pollution levels, as well as cause air quality impacts during the construction and operational phases.

3.2 Construction Phase Assessment

3.2.1 There is the potential for fugitive dust emissions to occur as a result of construction phase activities. These have been assessed in accordance with the methodology outlined within the Institute of Air Quality Management (IAQM) document 'Guidance on the Assessment of Dust from Demolition and Construction V1.1'⁶.

3.2.2 Activities on the proposed construction site have been divided into four types to reflect their different potential impacts. These are:

- Demolition;
- Earthworks;
- Construction; and,
- Trackout.

3.2.3 The potential for dust emissions was assessed for each activity that is likely to take place and considered three separate dust effects:

- Annoyance due to dust soiling;
- Harm to ecological receptors; and,
- The risk of health effects due to a significant increase in exposure to PM₁₀.

3.2.4 The assessment steps are detailed below.

⁶ Guidance on the Assessment of Dust from Demolition and Construction V1.1, IAQM, 2016.

Step 1

3.2.5 Step 1 screens the requirement for a more detailed assessment. Should human receptors be identified within 350m from the boundary or 50m from the construction vehicle route up to 500m from the site entrance, then the assessment proceeds to Step 2. Additionally, should ecological receptors be identified within 50m of the site or the construction vehicle route up to 500m from the site entrance, then the assessment also proceeds to Step 2.

3.2.6 Should sensitive receptors not be present within the relevant distances then **negligible** impacts would be expected and further assessment is not necessary.

Step 2

3.2.7 Step 2 assesses the risk of potential dust impacts. A site is allocated a risk category based on two factors:

- The scale and nature of the works, which determines the magnitude of dust arising as: small, medium or large (Step 2A); and,
- The sensitivity of the area to dust impacts, which can be defined as low, medium or high sensitivity (Step 2B).

3.2.8 The two factors are combined in Step 2C to determine the risk of dust impacts without mitigation applied.

3.2.9 Step 2A defines the potential magnitude of dust emission through the construction phase. The relevant criteria are summarised in Table 3.

Table 3 Construction Dust - Magnitude of Emission

Magnitude	Activity	Criteria
Large	Demolition	• Total volume of building to be demolished greater than 50,000m³ • Potentially dusty material (e.g. concrete) • On-site crushing and screening • Demolition activities more than 20m above ground level

Magnitude	Activity	Criteria
	Earthworks	- Total site area greater than 10,000m² - Potentially dusty soil type (e.g. clay, which will be prone to suspension when dry due to small particle size) - More than 10 heavy earth moving vehicles active at any one time - Formation of bunds greater than 8m in height - More than 100,000 tonnes of material moved
	Construction	- Total building volume greater than 100,000m³ - On site concrete batching - Sandblasting
	Trackout	- More than 50 Heavy Duty Vehicle (HDV) trips per day - Potentially dusty surface material (e.g. high clay content) - Unpaved road length greater than 100m
Medium	Demolition	- Total volume of building to be demolished between 20,000m³ and 50,000m³ - Potentially dusty construction material - Demolition activities 10m to 20m above ground level
	Earthworks	- Total site area 2,500m² to 10,000m² - Moderately dusty soil type (e.g. silt) 5 to 10 heavy earth moving vehicles active at any one time - Formation of bunds 4m to 8m in height - Total material moved 20,000 tonnes to 100,000 tonnes
	Construction	- Total building volume 25,000m³ to 100,000m³ - Potentially dusty construction material (e.g. concrete) - On site concrete batching
	Trackout	10 to 50 HDV trips per day - Moderately dusty surface material (e.g. high clay content) - Unpaved road length 50m to 100m
Small	Demolition	- Total volume of building to be demolished less than 20,000m³ - Construction material with low potential for dust release (e.g. metal cladding or timber) - Demolition activities less than 10m above ground and during wetter months

Magnitude	Activity	Criteria
	Earthworks	- Total site area less than 2,500m² - Soil type with large grain size (e.g. sand) - Less than 5 heavy earth moving vehicles active at any one time - Formation of bunds less than 4m in height - Total material moved less than 20,000 tonnes - Earthworks during wetter months
	Construction	- Total building volume less than 25,000m³ - Construction material with low potential for dust release (e.g. metal cladding or timber)
	Trackout	- Less than 10 HDV trips per day - Surface material with low potential for dust release - Unpaved road length less than 50m

3.2.10 Step 2B defines the sensitivity of the area around the development to potential dust impacts. The influencing factors are shown in Table 4.

Table 4 Construction Dust - Examples of Factors Defining Sensitivity of an Area

Receptor Sensitivity	Examples	
	Human Receptors	Ecological Receptors
High	- Users expect high levels of amenity - High aesthetic or value property - People expected to be present continuously for extended periods of time - Locations where members of the public are exposed over a time period relevant to the AQO for PM₁₀. e.g. residential properties, hospitals, schools and residential care homes	Internationally or nationally designated site e.g. Special Area of Conservation
Medium	- Users would expect to enjoy a reasonable level of amenity - Aesthetics or value of their property could be diminished by soiling - People or property wouldn't reasonably be expected to be present here continuously or regularly for extended periods as part of the normal pattern of use of the land e.g. parks and places of work	Nationally designated site e.g. Sites of Special Scientific Interest

Receptor Sensitivity	Examples	
	Human Receptors	Ecological Receptors
Low	• Enjoyment of amenity would not reasonably be expected • Property would not be expected to be diminished in appearance • Transient exposure, where people would only be expected to be present for limited periods. e.g. public footpaths, shopping streets, playing fields, farmland, short term car parks and roads	• Locally designated site e.g. Local Nature Reserve

3.2.11 The guidance also provides the following factors to consider when determining the sensitivity of an area to potential dust impacts:

- Any history of dust generating activities in the area;
- The likelihood of concurrent dust generating activity on nearby sites;
- Any pre-existing screening between the source and receptors;
- Any conclusions drawn from analysing local meteorological data which accurately represent the area; and if relevant the season during which works will take place;
- Any conclusions drawn from local topography;
- Duration of the potential impact, as a receptor may become more sensitive over time; and,
- Any known specific receptor sensitivities which go beyond the classifications given in the document.

3.2.12 These factors were considered in the undertaking of this assessment.

3.2.13 The criteria for determining the sensitivity of the area to dust soiling effects on people and property is summarised in Table 5.

Table 5 Construction Dust - Sensitivity of the Area to Dust Soiling Effects on People and Property

Receptor Sensitivity	Number of Receptors	Distance from the Source (m)			
		Less than 20	Less than 50	Less than 100	Less than 350
High	More than 100	High	High	Medium	Low
	10 - 100	High	Medium	Low	Low

Receptor Sensitivity	Number of Receptors	Distance from the Source (m)			
		Less than 20	Less than 50	Less than 100	Less than 350
	1 - 10	Medium	Low	Low	Low
Medium	More than 1	Medium	Low	Low	Low
Low	More than 1	Low	Low	Low	Low

3.2.14 Table 6 outlines the criteria for determining the sensitivity of the area to human health impacts.

Table 6 Construction Dust - Sensitivity of the Area to Human Health Impacts

Receptor Sensitivity	Background Annual Mean PM ₁₀ Concentration	Number of Receptors	Distance from the Source (m)				
			Less than 20	Less than 50	Less than 100	Less than 200	Less than 350
High	Greater than 32µg/m ³	More than 100	High	High	High	Medium	Low
		10 - 100	High	High	Medium	Low	Low
		1 - 10	High	Medium	Low	Low	Low
	28 - 32µg/m ³	More than 100	High	High	Medium	Low	Low
		10 - 100	High	Medium	Low	Low	Low
		1 - 10	High	Medium	Low	Low	Low
	24 - 28µg/m ³	More than 100	High	Medium	Low	Low	Low
		10 - 100	High	Medium	Low	Low	Low
		1 - 10	Medium	Low	Low	Low	Low
	Less than 24µg/m ³	More than 100	Medium	Low	Low	Low	Low
		10 - 100	Low	Low	Low	Low	Low
		1 - 10	Low	Low	Low	Low	Low
Medium	Greater than 32µg/m ³	More than 10	High	Medium	Low	Low	Low
		1 - 10	Medium	Low	Low	Low	Low

Receptor Sensitivity	Background Annual Mean PM ₁₀ Concentration	Number of Receptors	Distance from the Source (m)				
			Less than 20	Less than 50	Less than 100	Less than 200	Less than 350
	28 - 32µg/m ³	More than 10	Medium	Low	Low	Low	Low
		1 - 10	Low	Low	Low	Low	Low
	24 - 28µg/m ³	More than 10	Low	Low	Low	Low	Low
		1 - 10	Low	Low	Low	Low	Low
	Less than 24µg/m ³	More than 10	Low	Low	Low	Low	Low
		1 - 10	Low	Low	Low	Low	Low
Low	-	1 or more	Low	Low	Low	Low	Low

3.2.15 Table 7 outlines the criteria for determining the sensitivity of the area to ecological impacts.

Table 7 Construction Dust - Sensitivity of the Area to Ecological Impacts

Receptor Sensitivity	Distance from the Source (m)	
	Less than 20	Less than 50
High	High	Medium
Medium	Medium	Low
Low	Low	Low

3.2.16 Step 2C combines the dust emission magnitude with the sensitivity of the area to determine the risk of unmitigated impacts.

3.2.17 Table 8 outlines the risk category from demolition activities.

Table 8 Construction Dust - Dust Risk Category from Demolition Activities

Receptor Sensitivity	Dust Emission Magnitude		
	Large	Medium	Small
High	High	Medium	Medium
Medium	High	Medium	Low
Low	Medium	Low	Negligible

3.2.18 Table 9 outlines the risk category from earthworks and construction activities.

Table 9 Construction Dust - Dust Risk Category from Earthworks and Construction Activities

Receptor Sensitivity	Dust Emission Magnitude		
	Large	Medium	Small
High	High	Medium	Low
Medium	Medium	Medium	Low
Low	Low	Low	Negligible

3.2.19 Table 10 outlines the risk category from trackout activities.

Table 10 Construction Dust - Dust Risk Category from Trackout Activities

Receptor Sensitivity	Dust Emission Magnitude		
	Large	Medium	Small
High	High	Medium	Low
Medium	Medium	Low	Negligible
Low	Low	Low	Negligible

Step 3

3.2.20 Step 3 requires the identification of site specific mitigation measures within the IAQM guidance⁷ to reduce potential dust impacts based upon the relevant risk categories identified in Step 2. For sites with **negligible** risk, mitigation measures beyond those required by legislation are not required. However, additional controls may be applied as part of good practice.

Step 4

3.2.21 Once the risk of dust impacts has been determined and the appropriate mitigation measures identified, the final step is to determine the significance of any residual impacts. For almost all construction activity, the aim should be to control effects through the use of effective mitigation. Experience shows that this is normally possible. Hence the residual effect will normally be **not significant**.

3.2.22 The determination of significance relies on professional judgement and reasoning should be provided as far as practicable. The IAQM guidance suggests the provision of details of the assessor's qualifications and experience. These are provided in Appendix 2.

3.3 Operational Phase Assessment

Potential Future Exposure

3.3.1 The proposals have the potential to expose future occupants to elevated pollution levels. In order to assess NO₂, PM₁₀ and PM_{2.5} concentrations across the development site, detailed dispersion modelling was undertaken. Reference should be made to Appendix 1 for a full description of the assessment input data.

3.3.2 The dispersion modelling results were compared against the relevant AQOs and AQLV in order to determine the potential for exposure of future occupants to elevated pollutant concentrations and identify appropriate mitigation, if necessary.

⁷ Guidance on the Assessment of Dust from Demolition and Construction V1.1, IAQM, 2016.

Potential Development Impacts

- 3.3.3 The development has the potential to increase concentrations of NO₂, PM₁₀ and PM_{2.5} as a result of road traffic exhaust emissions associated with vehicles travelling to and from the site during the operational phase. An assessment was therefore undertaken using the criteria contained within the IAQM 'Land-Use Planning & Development Control: Planning for Air Quality'⁸ guidance to determine the potential for trips generated by the development to affect local air quality.
- 3.3.4 The following criteria are provided to help establish when an assessment of potential road traffic impacts on the local area is likely to be considered necessary:
- A change of Light Duty Vehicle (LDV) flows of more than 100 Annual Average Daily Traffic (AADT) within or adjacent to an AQMA or more than 500 AADT elsewhere;
 - A change of HDV flows of more than 25 AADT within or adjacent to an AQMA or more than 100 AADT elsewhere;
 - Realignment of roads where the change is 5m or more and the road is within an AQMA; or,
 - Introduction of a new junction or removal of an existing junction near to relevant receptors.
- 3.3.5 Should these criteria not be met, then the IAQM guidance⁹ considers air quality impacts associated with a scheme to be **not significant** and no further assessment is required.
- 3.3.6 Should screening of the relevant data indicate that any of the above criteria are met, then potential impacts at sensitive receptor locations can be assessed by calculating the change in pollutant concentrations as a result of the proposed development. The significance of predicted impacts can then be determined in accordance with the methodology outlined in the IAQM guidance¹⁰.

⁸ Land-Use Planning & Development Control: Planning for Air Quality, IAQM, 2017.

⁹ Land-Use Planning & Development Control: Planning for Air Quality, IAQM, 2017.

¹⁰ Land-Use Planning & Development Control: Planning for Air Quality, IAQM, 2017.

4.0 BASELINE

4.1 Introduction

- 4.1.1 Existing air quality conditions in the vicinity of the development site were identified in order to provide a baseline for assessment. These are detailed in the following Sections.

4.2 Local Air Quality Management

- 4.2.1 As required by the Environment Act (1995), RBC has undertaken Review and Assessment of air quality within their area of jurisdiction. This process has indicated that annual mean NO₂ concentrations are above the AQO within the borough. As such, a number of roads within Rochdale have been included within the Greater Manchester Combined Authority (GMCA) AQMA. This is described as follows:

"This is the part of the Greater Manchester Combined Authority AQMA located within the Rochdale Council area."

- 4.2.2 The development is located approximately 300m west of the AQMA. As such, there is the potential for vehicles travelling to and from the site to increase pollution levels in this sensitive area. This has been considered throughout the assessment.
- 4.2.3 RBC has concluded that concentrations of all other pollutants considered within the AQS are currently below the relevant AQOs. As such, no further AQMA's have been designated.

4.3 Air Quality Monitoring

- 4.3.1 Monitoring of pollutant concentrations is undertaken by RBC throughout their area of jurisdiction. Recent NO₂ results recorded in the vicinity of the development are shown in Table 11.

Table 11 Monitoring Results

Monitoring Site		Monitored Annual Mean NO ₂ Concentration (µg/m ³)		
		2018	2019	2020
RO4ANO	Middleton Library	26.7	33.2	22.2
RO25ANO	Oldham Road, Middleton	-(a)	34.7	25.9

Note: (a) Monitor commissioned in 2019.

4.3.2 As shown in Table 11, annual mean NO₂ concentrations were below the AQO of 40µg/m³ at both survey positions in recent years. Reference should be made to Figure 2 for a map of the monitoring positions.

4.3.3 It should be noted that pollutant concentrations recorded during 2020 are lower than 2019 due to a reduction in traffic and associated emissions caused by the COVID-19 pandemic. The results should therefore be viewed with caution.

4.3.4 RBC do not undertake PM₁₀ or PM_{2.5} monitoring in the vicinity of the site.

4.4 Background Pollutant Concentrations

4.4.1 Predictions of background pollutant concentrations on a 1km by 1km grid basis have been produced by DEFRA for the entire of the UK to assist LAs in their Review and Assessment of air quality. The proposed development site is located in grid square NGR: 386500, 405500. Data for this location was downloaded from the DEFRA website¹¹ for the purpose of the assessment and is summarised in Table 12.

Table 12 Background Pollutant Concentration Predictions

Pollutant	Predicted Background Pollutant Concentration (µg/m ³)		
	2019	2023	2026
NO ₂	18.25	15.43	13.85
PM ₁₀	12.13	11.56	11.35
PM _{2.5}	8.25	7.85	7.68

¹¹ <http://uk-air.defra.gov.uk/data/laqm-background-maps?year=2018>.

4.4.2 As shown in Table 12, predicted background NO₂, PM₁₀ and PM_{2.5} concentrations are below the relevant AQOs and AQLV at the development site.

4.5 **Sensitive Receptors**

4.5.1 A sensitive receptor is defined as any location which may be affected by changes in air quality as a result of a development. Receptors sensitive to potential dust impacts during demolition, earthworks and construction were identified from a desk-top study of the area up to 350m from the development boundary. These are summarised in Table 13.

Table 13 Demolition, Earthworks and Construction Dust Sensitive Receptors

Distance from Site Boundary (m)	Approximate Number of Human Receptors	Approximate Number of Ecological Receptors
Up to 20	10 - 100	1
Up to 50	10 - 100	1
Up to 100	More than 100	-
Up to 350	More than 100	-

4.5.2 Receptors sensitive to potential dust impacts from trackout were identified from a desk-top study of the area up to 50m from the road network within 500m of the site access. These are summarised in Table 14.

Table 14 Trackout Dust Sensitive Receptors

Distance from Site Access Route (m)	Approximate Number of Human Receptors	Approximate Number of Ecological Receptors
Up to 20	More than 100	1
Up to 50	More than 100	1

4.5.3 The ecological receptor identified in Table 13 and Table 14 is Alkrington Woods Local Nature Reserve (LNR), which lies approximately 15m to the south of the site boundary. Reference should be made to Figure 3 for a map of the designation extents.

4.5.4 A number of additional factors have been considered when determining the sensitivity of the surrounding area. These are summarised in Table 15.

Table 15 Additional Area Sensitivity Factors to Potential Dust Impacts

Guidance	Comment
Whether there is any history of dust generating activities in the area	The baseline review did not indicate any dust generating activities in the local area
The likelihood of concurrent dust generating activity on nearby sites	A review of the planning portal did not indicate any additional development proposals likely to result in concurrent dust generation in the vicinity of the site
Pre-existing screening between the source and the receptors	Trees and shrubs are located sporadically along the southern and western boundary of the site. These may act as a barrier between emission sources and receptors.
Conclusions drawn from analysing local meteorological data which accurately represent the area: and if relevant the season during which works will take place	As shown in Figure 4, the predominant wind bearing at the site is from the south, with significant frequencies from the west. As such, receptors to the south and east are most likely to be affected by dust releases
Conclusions drawn from local topography	There are no significant topographical constraints to dust dispersion
Duration of the potential impact, as a receptor may become more sensitive over time	Currently it is unclear as to the duration of the construction phase. However, it is possible that it will extend over one year. The sensitivity of nearby receptors is unlikely to change during this time
Any known specific receptor sensitivities which go beyond the classifications given in the document	No specific receptor sensitivities identified during the baseline assessment

4.5.5 Based on the criteria shown in Table 15, the sensitivity of the receiving environment to potential dust impacts was determined as **high**. This was because the identified receptors included residential properties.

4.5.6 As the identified ecological receptor is a LNR, the sensitivity was classified as **low**.

4.5.7 The sensitivity of the receiving environment to specific potential dust impacts, based on the criteria shown in Section 3.2, is shown in Table 16.

Table 16 Sensitivity of the Surrounding Area to Potential Dust Impacts

Potential Impact	Sensitivity of the Surrounding Area			
	Demolition	Earthworks	Construction	Trackout
Dust Soiling	High	High	High	High
Human Health	Low	Low	Low	Medium
Ecological	Low	Low	Low	Low

5.0 ASSESSMENT

5.1 Introduction

- 5.1.1 The proposal has the potential to expose future occupants to elevated pollution levels, as well as cause adverse air quality impacts at sensitive locations. These factors are assessed in the following Sections.

5.2 Construction Phase Assessment

Step 1

- 5.2.1 The undertaking of activities such as demolition, excavation, ground works, cutting, construction and storage of materials has the potential to result in fugitive dust emissions throughout the construction phase. Vehicle movements on the local road network also have the potential to result in the re-suspension of dust from highway surfaces.
- 5.2.2 The potential for impacts at sensitive locations depends significantly on local meteorology during the undertaking of dust generating activities, with the most significant effects likely to occur during dry and windy conditions.
- 5.2.3 The desk-study undertaken to inform the baseline identified a number of sensitive receptors within 350m of the site boundary. As such, a detailed assessment of potential dust impacts was required.

Step 2

Demolition

- 5.2.4 Demolition will involve clearance of the existing buildings on site. It is estimated that the total building volume to be demolished is less than 20,000m³. In accordance with the criteria outlined in Table 3, the magnitude of potential dust emissions from demolition is therefore **small**.

5.2.5 Table 16 indicates the sensitivity of the area to dust soiling effects on people and property is **high**. In accordance with the criteria outlined in Table 8, the development is considered to be a **medium** risk site for dust soiling as a result of demolition activities.

5.2.6 Table 16 indicates the sensitivity of the area to human health impacts is **low**. In accordance with the criteria outlined in Table 9, the development is considered to be a **negligible** risk site for human health impacts as a result of demolition activities.

5.2.7 Table 16 indicates the sensitivity of the area to ecological impacts is **low**. In accordance with the criteria outlined in Table 9, the development is considered to be a **negligible** risk site for ecological impacts as a result of demolition activities.

Earthworks

5.2.8 Earthworks may involve excavating material, haulage, tipping and stockpiling. The area of the proposed development site is greater than 10,000m². In accordance with the criteria outlined in Table 3, the magnitude of potential dust emissions from earthworks is therefore **large**.

5.2.9 Table 16 indicates the sensitivity of the area to dust soiling effects on people and property is **high**. In accordance with the criteria outlined in Table 9, the development is considered to be a **high** risk site for dust soiling as a result of earthworks.

5.2.10 Table 16 indicates the sensitivity of the area to human health impacts is **low**. In accordance with the criteria outlined in Table 9, the development is considered to be a **low** risk site for human health impacts as a result of earthworks.

5.2.11 Table 16 indicates the sensitivity of the area to ecological impacts is **low**. In accordance with the criteria outlined in Table 9, the development is considered to be a **low** risk site for ecological impacts as a result of earthworks.

Construction

5.2.12 Due to the size of the development, the total building volume will be between 25,000m³ and 100,000m³. In accordance with the criteria outlined in Table 3, the magnitude of potential dust emissions from construction is therefore **medium**.

5.2.13 Table 16 indicates the sensitivity of the area to dust soiling effects on people and property is **high**. In accordance with the criteria outlined in Table 9, the development is considered to be a **medium** risk site for dust soiling as a result of construction activities.

5.2.14 Table 16 indicates the sensitivity of the area to human health impacts is **low**. In accordance with the criteria outlined in Table 9, the development is considered to be a **low** risk site for human health impacts as a result of construction activities.

5.2.15 Table 16 indicates the sensitivity of the area to ecological impacts is **low**. In accordance with the criteria outlined in Table 9, the development is considered to be a **low** risk site for ecological impacts as a result of construction activities.

Trackout

5.2.16 Based on the site area and existing hardstanding, it is anticipated that the unpaved road length will be less than 50m. In accordance with the criteria outlined in Table 3, the magnitude of potential dust emissions from trackout is therefore **small**.

5.2.17 Table 16 indicates the sensitivity of the area to dust soiling effects to people and property is **high**. In accordance with the criteria outlined in Table 10, the development is considered to be a **low** risk site for dust soiling as a result of trackout activities.

5.2.18 Table 16 indicates the sensitivity of the area to human health impacts is **medium**. In accordance with the criteria outlined in Table 10, the development is considered to be a **negligible** risk site for human health impacts as a result of trackout activities.

5.2.19 Table 16 indicates the sensitivity of the area to ecological impacts is **low**. In accordance with the criteria outlined in Table 9, the development is considered to be a **negligible** risk site for ecological impacts as a result of trackout activities.

Summary of the Risk of Dust Effects

5.2.20 A summary of the risk from each dust generating activity is provided in Table 17.

Table 17 Summary of Potential Unmitigated Dust Risks

Potential Impact	Risk			
	Demolition	Earthworks	Construction	Trackout
Dust Soiling	Medium	High	Medium	Low
Human Health	Negligible	Low	Low	Negligible
Ecological	Negligible	Low	Low	Negligible

5.2.21 As indicated in Table 17, the potential risk of dust soiling is **high** from earthworks, **medium** from demolition and construction and **low** from trackout. The potential risk of human health effects is **low** from earthworks and construction and **negligible** from demolition and trackout. The potential risk of ecological effects is **low** from earthworks and construction and **negligible** from demolition and trackout.

5.2.22 It should be noted that the potential for impacts depends significantly on the distance between the dust generating activity and receptor location. Risk was predicted based on a worst-case scenario of works being undertaken at the site boundary closest to each sensitive area. Therefore, actual risk is likely to be lower than that predicted during the majority of the construction phase.

Step 3

5.2.23 The IAQM guidance¹² provides potential mitigation measures to reduce impacts as a result of fugitive dust emissions during the construction phase. These have been adapted for the development site as summarised in Table 18. These may be reviewed prior to the commencement of construction works and incorporated into a Construction Environmental Management Plan or similar if required by the LA.

¹² Guidance on the Assessment of Dust from Demolition and Construction V1.1, IAQM, 2017.

Table 18 Fugitive Dust Emission Mitigation Measures

Issue	Control Measure
Communications	• Develop and implement a stakeholder communications plan that includes community engagement before work commences on site. • Display the name and contact details of person(s) accountable for air quality and dust issues on the site boundary. This may be the environment manager/engineer or the site manager • Display the head or regional office contact information • Develop and implement a Dust Management Plan (DMP) or similar, which may include measures to control other emissions, approved by the LA
Site management	• Record all dust and air quality complaints, identify cause(s), take appropriate measures to reduce emissions in a timely manner, and record the measures taken • Make the complaints log available to the LA upon request • Record any exceptional incidents that cause dust and/or air emissions, either on- or off- site, and the action taken to resolve the situation in the log book
Monitoring	• Carry out regular site inspections to monitor compliance with the DMP, record inspection results, and make an inspection log available to the LA upon request • Increase the frequency of site inspections when activities with a high potential to produce dust are being carried out and during prolonged dry or windy conditions
Site preparation	• Plan site layout so that machinery and dust causing activities are located away from receptors, as far as is possible • Erect solid screens or barriers around dusty activities or the site boundary that are at least as high as any stockpiles on site • Fully enclose specific operations where there is a high potential for dust production and they are active for an extensive period • Avoid site runoff of water or mud • Keep site fencing, barriers and scaffolding clean using wet methods • Remove materials that have a potential to produce dust from site as soon as possible, unless being re-used • Cover, seed or fence stockpiles to prevent wind whipping
Operating vehicle/machinery and sustainable travel	• Ensure all vehicles switch off engines when stationary - no idling vehicles • Avoid the use of diesel or petrol powered generators and use mains electricity or battery powered equipment where practicable

Issue	Control Measure
Operations	• Only use cutting, grinding or sawing equipment fitted or in conjunction with suitable dust suppression techniques • Ensure an adequate water supply on the site for effective dust suppression, using non-potable water where possible and appropriate • Use enclosed chutes and conveyors and covered skips • Minimise drop heights and use fine water sprays wherever appropriate • Ensure equipment is available to clean any dry spillages, and clean up spillages as soon as reasonably practicable using wet cleaning methods
Waste management	• No bonfires and burning of waste materials
Demolition	• Ensure effective water suppression is used during demolition operations • Avoid explosive blasting, using appropriate manual or mechanical alternatives • Bag and remove any biological debris or damp down such material before demolition
Earthworks	• Re-vegetate earthworks and exposed areas/soil stockpiles to stabilise surfaces • Use Hessian, mulches or trackifiers where it is not possible to re-vegetate or cover with topsoil • Only remove secure covers in small areas during work and not all at once
Construction	• Avoid scabbling (roughening of concrete surfaces), if possible • Ensure sand and other aggregates are stored in bunded areas and are not allowed to dry out • Ensure bulk cement and other fine powder materials are delivered in enclosed tankers and stored in silos with suitable emission control systems to prevent escape of material and overfilling during delivery
Trackout	• Use water-assisted dust sweeper on access and local roads, if required • Avoid dry sweeping of large areas • Ensure vehicles entering and leaving site are covered to prevent escape of materials • Implement a wheel washing system, if required

Step 4

- 5.2.24 Assuming the relevant mitigation measures outlined in Table 18 are implemented, the residual impact from all dust generating activities is predicted to be **not significant**, in accordance with the IAQM guidance¹³.

5.3 Operational Phase Assessment

Potential Future Exposure

- 5.3.1 The proposed development has the potential to expose future occupants to elevated pollution levels. Dispersion modelling was therefore undertaken with the inputs described in Appendix 1 to quantify air quality conditions at the site. Reference should be made to Figures 5, 6 and 7 for graphical representations of predicted annual mean NO₂, PM₁₀ and PM_{2.5} concentrations.
- 5.3.2 As shown in Figure 5, annual mean NO₂ concentrations were predicted to be below the AQO of 40µg/m³ at the site boundary. The maximum level was 34.25µg/m³.
- 5.3.3 As shown in Figure 6, annual mean PM₁₀ concentrations were predicted to be below the AQO of 40µg/m³ at the site boundary. The maximum level was 15.40µg/m³.
- 5.3.4 As shown in Figure 7, annual mean PM_{2.5} concentrations were predicted to be below the AQLV of 20µg/m³ at the site boundary. The maximum level was 10.20µg/m³.
- 5.3.5 Based on the assessment results, future occupants are not predicted to be exposed to pollutant concentrations above the relevant AQOs and AQLV. As such, the site is considered suitable for the proposed use from an air quality perspective.

Potential Development Impacts

- 5.3.6 Any vehicle movements associated with the development will generate exhaust emissions on the local and regional road networks. Information provided by Eddisons, the

¹³ Guidance on the Assessment of Dust from Demolition and Construction V1.1, IAQM, 2016.

Transport Consultants for the project, indicated that the proposals are anticipated to generate 98 vehicle movements per day.

- 5.3.7 Based on the provided information, the proposals are not anticipated to result in an increase of LDV flows of more than 500 AADT on any individual road link, or 100 AADT within the AQMA, include significant highway realignment or the introduction of a junction and there will not be a requirement for more than 25 HDV deliveries per day. As such, potential air quality impacts associated with operational phase road vehicle exhaust emissions are predicted to be **not significant**, in accordance with the IAQM¹⁴ screening criteria shown in Section 3.3.

¹⁴ Land-Use Planning & Development Control: Planning for Air Quality, IAQM, 2017.

6.0 CONCLUSION

- 6.1.1 Redmore Environmental Ltd was commissioned by Muller Property Group to undertake an Air Quality Assessment in support of a mixed-use development on land off Old Manchester Road, Middleton.
- 6.1.2 The development may lead to the exposure of future occupants to any existing air quality issues at the site, as well as adverse impacts at sensitive locations during the construction and operational phases. As such, an Air Quality Assessment was undertaken in order to determine baseline conditions, consider location suitability for the proposed end-use and assess potential effects associated with the scheme.
- 6.1.3 During the construction phase of the development there is the potential for air quality impacts as a result of fugitive dust emissions from the site. These were assessed in accordance with the IAQM methodology. Assuming good practice dust control measures are implemented, the residual significance of potential air quality impacts from dust generated by demolition, earthworks, construction and trackout activities was predicted to be **not significant**.
- 6.1.4 The proposal has the potential to expose future occupants to elevated pollution levels. Dispersion modelling was therefore undertaken using ADMS-Roads in order to predict concentrations as a result of emissions from the local highway network. Results were subsequently verified using local monitoring data.
- 6.1.5 The results of the dispersion modelling assessment indicated that predicted annual mean NO₂, PM₁₀ and PM_{2.5} concentrations were below the relevant AQOs and AQLV at the development boundary. As such, the site is considered suitable for the proposed end use from an air quality perspective.
- 6.1.6 Potential impacts during the operational phase of the proposed development may occur due to road traffic exhaust emissions associated with vehicles travelling to and from the site. These were assessed against the screening criteria provided within the IAQM¹⁵ guidance. Due to the limited number of anticipated vehicle trips associated with the proposals, road traffic exhaust impacts were predicted to be **not significant**.


¹⁵ Land-Use Planning & Development Control: Planning for Air Quality, IAQM, 2017.


6.1.7 Based on the assessment results, air quality factors are not considered a constraint to planning consent for the development.


7.0 **ABBREVIATIONS**

AADT	Annual Average Daily Traffic
ADM	Atmospheric Dispersion Modelling
AQLV	Air Quality Limit Value
AQMA	Air Quality Management Area
AQO	Air Quality Objective
AQS	Air Quality Strategy
CERC	Cambridge Environmental Research Consultants
DEFRA	Department for Environment, Food and Rural Affairs
DfT	Department for Transport
DMP	Dust Management Plan
EB	Eastbound
GMCA	Greater Manchester Combined Authority
HDV	Heavy Duty Vehicle
IAQM	Institute of Air Quality Management
LA	Local Authority
LAQM	Local Air Quality Management
LDV	Light Duty Vehicle
LNR	Local Nature Reserve
NGR	National Grid Reference
NO ₂	Nitrogen dioxide
NO _x	Oxides of nitrogen
NPPF	National Planning Policy Framework
NPPG	National Planning Policy Guidance
PM ₁₀	Particulate matter with an aerodynamic diameter of less than 10µm
PM _{2.5}	Particulate matter with an aerodynamic diameter of less than 2.5µm
RBC	Rochdale Borough Council
SP	Slow Phase
WB	Westbound
Z ₀	Roughness length

Figures







Legend

-  Site Boundary
-  Ecological Receptor

Title

Figure 3 - Construction Phase Dust Emission Ecological Receptor Extents

Project

Air Quality Assessment - Old Manchester Road, Middleton

Project Reference

6290


Client

Muller Property Group

Contains Ordnance Survey data
© Crown copyright and database right 2022



www.red-env.co.uk | 0161 7060075



Legend

Title

Figure 4 - Wind Rose of 2019
Manchester Airport
Meteorological Data

Project

Air Quality Assessment -
Old Manchester Road, Middleton

Project Reference


6290

Client

Muller Property Group




www.red-env.co.uk | 0161 7060075



Legend



Site Boundary



Annual Mean NO₂
Concentration
(µg/m³)

Title

Figure 5 - Predicted Annual Mean
NO₂ Concentrations (µg/m³)

Project

Air Quality Assessment -
Old Manchester Road, Middleton

Project Reference

6290


Client


Muller Property Group

Contains Ordnance Survey data
© Crown copyright and database right 2022



www.red-env.co.uk | 0161 7060075






Legend



Site Boundary



Annual Mean PM_{2.5}
Concentration
(µg/m³)

Title

Figure 7 - Predicted Annual Mean
PM_{2.5} Concentrations (µg/m³)

Project

Air Quality Assessment -
Old Manchester Road, Middleton

Project Reference

6290


Client

Muller Property Group

Contains Ordnance Survey data
© Crown copyright and database right 2022



www.red-env.co.uk | 0161 7060075



Appendix 1 - Assessment Input Data

Introduction

The proposals have the potential to expose future occupants to elevated pollution levels. In order to assess NO₂, PM₁₀ and PM_{2.5} concentrations across the development site, dispersion modelling was undertaken in accordance with the following methodology.

Modelling was undertaken for 2019 to allow verification against recent monitoring results and 2026 to represent likely conditions in the opening year of the scheme.

Dispersion Model

Dispersion modelling was undertaken using the ADMS-Roads dispersion model (version 5.0.1.3). ADMS-Roads is developed by Cambridge Environmental Research Consultants (CERC) and is routinely used throughout the world for the prediction of pollutant dispersion from road sources. Modelling predictions from this software package are accepted within the UK by the Environment Agency and DEFRA.

The model requires input data that details the following parameters:

- Assessment area;
- Traffic flow data;
- Vehicle emission factors;
- Spatial co-ordinates of emissions;
- Street width;
- Meteorological data;
- Roughness length (z_0); and,
- Monin-Obukhov length.

The following Sections detail the relevant inputs utilised in the assessment.

Assessment Area

The assessment area was defined based on the location of the development and roads likely to impact pollutant levels across the site. Ambient concentrations were predicted over NGR: 386155, 405423 to 386401, 405669. One Cartesian grid was used within the model to produce data suitable for contour plotting using the Surfer software package. It should be noted that

although the grid only covered the proposed site, source geometries were extended in order to ensure the impact of all relevant emissions in the vicinity of the scheme were considered.

Reference should be made to Figure 8 for a graphical representation of the assessment grid extents.

Traffic Flow Data

Baseline traffic data for use in the assessment, including 24-hour AADT flows and fleet composition as HDV proportion, was obtained from the Department for Transport (DfT)¹⁶. The DfT web tool enables the user to view and download traffic flows on every link of the 'A' road and motorway network, as well as selected minor roads, in Great Britain for the years 1999 to 2021. It should be noted that the DfT web tool is referenced in DEFRA guidance¹⁷ as being a suitable source of data for air quality assessments and it is therefore considered to provide a reasonable estimate of traffic flows in the vicinity of the site.

The baseline traffic data was converted to the site opening year utilising a factor obtained from TEMPro (version 8.0). This software package has been developed by the DfT to calculate future traffic growth throughout the UK.

Road widths and vehicle speeds were estimated from aerial photography and UK highway design standards. A summary of the traffic data used in the assessment is provided in Table A1.1.

Table A1.1 Traffic Data

Link		24-hour AADT Flow		HDV Prop. Of Fleet (%)	Road Width (m)	Avg. Vehicle Speed (km/h)
		2019	2026			
L1	Manchester Old Road	14,406	15,321	4.05	8.3	45
L2	Manchester Old Road (Slow Phase) SP	14,406	15,321	4.05	15.0	25
L3	Manchester Old Road between Kemp Street and Barton Road westbound (WB) SP	15,430	16,410	2.70	7.1	25

¹⁶ <https://roadtraffic.dft.gov.uk/#6/55.254/-6.053/basemap-regions-countpoints>.

¹⁷ Local Air Quality Management Technical Guidance (TG22), DEFRA, 2022.

Link		24-hour AADT Flow		HDV Prop. Of Fleet (%)	Road Width (m)	Avg. Vehicle Speed (km/h)
		2019	2026			
L4	Manchester Old Road between Kemp Street and Barton Road WB	15,430	16,410	2.70	7.3	45
L5	Manchester Old Road between Kemp Street and Barton Road WB SP 2	15,430	16,410	2.70	6.7	25
L6	Manchester Old Road between Kemp Street and Barton Road eastbound (EB) Roundabout exit SP	10,429	11,091	5.79	6.9	25
L7	Manchester Old Road between Kemp Street and Barton Road EB	10,429	11,091	5.79	7.1	45
L8	Manchester Old Road between Kemp Street and Barton Road EB roundabout approach SP	10,429	11,091	5.79	7.9	25
L9	Manchester Old Road between Barton Road and Assheton Way EB roundabout exit SP	10,429	11,091	5.79	7.0	25
L10	Manchester Old Road between Barton Road and Assheton Way EB	10,429	11,091	5.79	8.3	45
L11	Manchester Old Road between Barton Road and Assheton Way EB roundabout approach SP	10,429	11,091	5.79	7.7	25
L12	Manchester Old Road between Barton Road and Assheton Way WB RB approach SP	15,430	16,410	2.70	8.0	25
L13	Manchester Old Road between Barton Road and Assheton Way WB	15,430	16,410	2.70	6.8	45
L14	Manchester Old Road between Barton Road and Assheton Way WB roundabout exit SP	15,430	16,410	2.70	6.6	25
L15	Oldham Road canyon 1	9,872	10,499	3.19	10.4	45
L16	Oldham Road	9,872	10,499	3.19	8.1	45
L17	Oldham Road canyon 2	9,872	10,499	3.19	9.0	45
L18	Oldham Road between RB and Townley Street	9,872	10,499	3.19	7.8	45
L19	Oldham Road RB entrance SP	4,792	5,096	3.21	6.6	25
L20	Oldham Road RB exit SP	4,313	4,587	3.04	7.9	25
L21	Oldham Road	9,872	10,499	3.19	8.1	45
R1	Manchester Old Road and Kemp Street Roundabout	11,021	11,720	2.70	10.2	25

Link		24-hour AADT Flow		HDV Prop. Of Fleet (%)	Road Width (m)	Avg. Vehicle Speed (km/h)
		2019	2026			
R2	Manchester Old Road and Manchester New Road Roundabout	51,718	55,002	5.79	9.0	25
R3	Manchester Old Road and Assheton Way Roundabout	8,741	9,296	2.70	10.5	25

Reference should be made to Figure 8 for a graphical representation of the road link locations.

Canyons

Where buildings or walls surround roads, pollutant dispersion patterns are altered which can lead to high pollutant concentrations. These street canyons can significantly influence air quality along a road and therefore it is important to take consideration of their effects when undertaking dispersion modelling.

The release of ADMS-Roads version 4.0.1.0 in December 2015 incorporated a number of new features including an advanced street canyon module, which have been retained in version 5.0.1.3. Advanced street canyon modelling allows a number of parameters to be included in the dispersion model in order to predict pollutant dispersion patterns which better reflect air flow within complex urban geometries.

Canyons have five principal effects on dispersion which can influence pollutant concentrations. These are:

- Pollutants are channelled along street canyons;
- Pollutants are dispersed across street canyons by circulating flow at road height;
- Pollutants are trapped in recirculation regions;
- Pollutants leave the canyon through gaps between buildings - as if there was no canyon; and,
- Pollutants leave the canyon from the canyon top.

The combined modelling of these effects will result in concentration patterns unique to each canyon. The parameters used in the assessment are outlined in Table A1.2. It should be noted

that where buildings are only present on one side of the road, parameters were purposely included at 0m.

Table A1.2 Canyon Parameters

Link	Parameter (m)					
	Canyon Width to Left	Average Height of Buildings to Left	Building Length Left	Canyon Width Right	Average Height of Buildings to Right	Building Length Right
L15	5.7	6.0	36.0	8.3	4.3	16.0
L16	6.3	5.7	418.0	8.2	5.7	408.0
L17	0.0	0.0	0.0	5.9	5.9	42.0

A choice of two modes is provided for use in the advanced canyon module. Standard mode assumes that each road is part of a continuous network of roads with similar canyon properties. Network mode analyses the road network to determine transport of pollutants between adjoining street canyons, allows for varying concentrations along the canyon and accounts for transport of pollutants out of the end of a canyon. Network mode is considered most accurate for detailed local analysis and as such was selected for use in the model.

Emission Factors

Emission factors for each link were calculated using the relevant traffic flows and the Emissions Factor Toolkit (version 11.0). This has been produced by DEFRA and incorporates COPERT 5.3 vehicle emission factors and fleet information.

There is current uncertainty over NO₂ concentrations within the UK, with the implementation of new vehicle emission standards not resulting in the previously expected reduction in roadside levels. Therefore, 2019 emission factors were utilised in preference to the development opening year in order to provide robust model outputs. As predictions for 2019 were verified, it is considered the results are a robust indication of worst case concentrations for the future year.

Meteorological Data

Meteorological data used in the assessment was taken from Manchester Airport meteorological station over the period 1st January 2019 to 31st December 2019 (inclusive). Manchester Airport is

located at NGR: 381792, 384116, which is approximately 12.6km south of the development. It is anticipated that conditions would be reasonably similar over a distance of this magnitude. The data was therefore considered suitable for an assessment of this nature.

All meteorological records used in the assessment were provided by Atmospheric Dispersion Modelling (ADM) Ltd, which is an established distributor of data within the UK. Reference should be made to Figure 4 for a wind rose of utilised meteorological data.

Roughness Length

The z_0 is a modelling parameter applied to allow consideration of surface height roughness elements. A z_0 of 1m was used to describe the modelling extents. This is considered appropriate for the morphology of the area and is suggested within ADMS-Roads as being suitable for 'cities and woodlands'.

A z_0 of 0.2m was used to describe the meteorological site. This value is considered appropriate for the morphology of the area and is suggested within ADMS-Roads as being suitable for 'agricultural areas (min)'.

Monin-Obukhov Length

The Monin-Obukhov length provides a measure of the stability of the atmosphere. A minimum Monin-Obukhov length of 30m was used to describe the modelling extents and meteorological site. This value is considered appropriate for the nature of both areas and is suggested within ADMS-Roads as being suitable for 'cities and large towns'.

Background Concentrations

Background concentrations used in the assessment were obtained from the DEFRA mapping study for the grid square containing the site. These are shown in Table 12.

Similarly to emission factors, background concentrations from 2019 were utilised in preference to the opening year. This provided a robust assessment and is likely to overestimate pollutant concentrations during the operation of the proposals.

NO_x to NO₂ Conversion

Predicted annual mean NO_x concentrations were converted to NO₂ concentrations using the spreadsheet (version 8.1) provided by DEFRA, which is the method detailed within DEFRA guidance¹⁸.

Verification

The predicted results from a dispersion model may differ from measured concentrations for a large number of reasons, including:

- Estimates of background concentrations;
- Uncertainties in source activity data such as traffic flows and emission factors;
- Variations in meteorological conditions;
- Overall model limitations; and,
- Uncertainties associated with monitoring data, including locations.

Model verification is the process by which these and other uncertainties are investigated and where possible minimised. In reality, the differences between modelled and monitored results are likely to be a combination of all of these aspects.

For the purpose of the assessment, model verification was undertaken for 2019 using traffic data, meteorological data and monitoring results from this year. The choice of 2019 as the verification year aligns with the IAQM position statement 'Use of 2020 and 2021 Monitoring Datasets'¹⁹, which states:

"If you are carrying out an air quality study that includes validation against monitoring data, use 2019 monitoring data as the last typical year"

Monitoring of NO₂ concentrations was undertaken at one location within the vicinity of roads included within the model during 2019. The result was obtained and the road contribution to total NO_x concentration calculated following the methodology contained within DEFRA guidance²⁰.

¹⁸ Local Air Quality Management Technical Guidance (TG22), DEFRA, 2022.

¹⁹ Use of 2020 and 2021 Monitoring Datasets, IAQM, 2021.

²⁰ Local Air Quality Management Technical Guidance (TG22), DEFRA, 2022.

The monitored annual mean NO₂ concentration and calculated road NO_x concentration is summarised in Table A1.3.

Table A1.3 NO_x Verification - Monitoring Result

Monitoring Location		Monitored NO ₂ Concentration (µg/m ³)	Calculated Road NO _x Concentration (µg/m ³)
RO25ANO	Oldham Road, Middleton	34.7	32.74

The annual mean road NO_x concentration predicted from the dispersion model and the 2019 road NO_x concentration calculated from the monitoring result is summarised in Table A1.4.

Table A1.4 NO_x Verification - Modelling Result

Monitoring Location		Calculated Road NO _x Concentration (µg/m ³)	Modelled Road NO _x Concentration (µg/m ³)
RO25ANO	Oldham Road, Middleton	32.74	17.22

The monitored and modelled road NO_x concentrations were compared to calculate the associated ratio. This indicated that a verification factor of 1.9013 was required to be applied to all road NO_x modelling results.

Monitoring of PM₁₀ or PM_{2.5} concentrations was not undertaken within the assessment extents. The NO_x verification factor was therefore used to adjust model predictions of these species in lieu of more accurate data in accordance with DEFRA guidance²¹.

²¹ Local Air Quality Management Technical Guidance (TG22), DEFRA, 2022.

Date: 8th March 2023

Ref: 6290

Appendix 2 - Curricula Vitae

KEY EXPERIENCE:

Jethro is a Chartered Environmentalist and Director of Redmore Environmental with specialist experience in the air quality and odour sectors. His key capabilities include:

- Production and management of Air Quality, Dust and Odour Assessments for a wide-range of clients from the retail, residential, infrastructure, commercial and industrial sectors.
- Production and co-ordination of Environmental Permit applications for a variety of industrial sectors.
- Detailed dispersion modelling of road vehicle and industrial emissions using ADMS-Roads, ADMS-5, AERMOD-PRIME and BREEZE-ROADS. Studies have included impact assessment of ground level pollutant and odour concentrations and assessment of suitability of development sites for proposed end-use.
- Project management and co-ordination of Environmental Impact Assessments and scoping reports for developments throughout the UK.
- Provision of expert witness services at Planning Inquiries.
- Design and project management of pollutant monitoring campaigns.
- Co-ordination and management of large-scale multi-disciplinary projects and submissions.
- Provision of expert advice to local government and international environmental bodies, as well as involvement in production of industry guidance.

SELECT PROJECTS SUMMARY:

Industrial

Shanks Waste Management - Odour Assessments of two waste management facilities to support Environmental Permit Applications.

Tatweer Petroleum - dispersion modelling of Bahrain oil field.

Doha South Sewage Treatment Works - AQA for works extension in Qatar.

IRIS Environmental Appraisal Report Reviews, Isle of Man Government - odour assessment reviews.

Lankem, Greater Manchester - Environmental Permit Application for chemical manufacturing plant.

Newport Docks Bulk Drying, Pelleting and CHP Facility - air quality EIA for gas CHP.

Springshades, Leicester - Environmental Permit Variation Application for textile manufacturing plant.

Valspar, Chester - Odour Assessment and production of Odour Management Plan for a paint manufacturing plant in response to neighbour complaints.

Agrivert - dispersion modelling of odour and CHP emissions from numerous AD plants.

James Cropper Paper Mill, Cumbria - air quality EIA, Environmental Permit Variation and Human Health Risk Assessment for new biomass boiler adjacent to SSSI.

Rigg Approach, Leyton - Air Quality Assessment in support of waste transfer site.

Lynchford Lane Waste Transfer Station - biomass facility energy recovery plant.

Barnes Wallis Heat and Power, Cobham - biomass facility adjacent to AQMA.

Residential

Wood St Mill, Bury - residential development adjacent to scrap metal yard.

Hyams Lane, Holbrook - Odour Assessment to support residential development adjacent to sewage works.

North Wharf Gardens, London - peer review of EIA undertaken for large residential development.

Loxford Road, Alford - Air Quality EIA for residential development, included consideration of impacts from associated package sewage works

Elephant and Castle Leisure Centre - baseline AQA for redevelopment.

Carr Lodge, Doncaster - EIA for large residential development.

Queensland Road, Highbury - residential scheme including CHP.

Bicester Ecotown - dispersion modelling of energy centre.

Castleford Growth Delivery Plan - baseline air quality constraints assessment for town redevelopment.

York St, Bury - residential development adjacent to AQMA.

Temple Point Leeds - residential development adjacent to M1.

Commercial and Retail

Etihad Stadium - Air Quality EIA for the extension to the capacity of the Etihad Stadium, Manchester.

Wakefield College - redevelopment of city centre campus in AQMA.

Manchester Airport Cargo Shed - commercial development.

Manchester Airport Apron Extension - EIA including aircraft emission modelling.

National Youth Theatre, Islington - redevelopment to provide new arts space and accommodation.

KEY EXPERIENCE:

Alec is a Graduate Environmental Consultant with specialist experience in the air quality sector. His key capabilities include:

- Production of Air Quality Assessments in accordance with Department for Environment, Food and Rural Affairs (DEFRA) methodologies for a range of residential, commercial and industrial sectors.
- Detailed dispersion modelling of road vehicle exhaust emissions using ADMS-Roads. Studies have included assessment of road traffic exhaust emissions on sensitive receptors and exposure of new residents to poor air quality
- Advanced Canyon Modelling to evaluate the impact of altered urban topography on air quality in built up areas
- Assessment of construction dust impacts from a range of development sizes
- Assessment of fugitive dust impacts from a range of mineral extraction developments
- Assessment of petrol stations to address benzene concentrations and their impact on adjacent developments
- Odour surveys to assess amenity and suitability of sites for potential future development for residential use

SELECT PROJECTS SUMMARY:

1 Piccadilly Circus, London

Air Quality Assessment in support of a tourist hostel located within an Air Quality Management Area (AQMA). The development had the potential to expose future occupants to elevated pollution levels and cause impacts at sensitive locations. Potential emissions from the proposals were also assessed to determine compliance with the Air Quality Neutral requirements of the London Plan. Results of the assessment indicated that the site was Air Quality Neutral and air quality factors were not a constraint to the development.

Kingscroft Farm, Havant

Air Quality Assessment in support of a residential development located in close proximity to the A27 and a number of gas-fired generator sites. The development had the potential to expose future residents to elevated pollution concentrations and cause impacts at sensitive locations. Detailed dispersion modelling was undertaken using ADMS-roads to assess pollutant concentrations across the development and a comparison was made between overall concentrations with and without the development in place. Results indicated pollutant concentrations were below the relevant standards across the site and impacts associated with the development were not significant.

Trademark House, Petersfield

Odour Assessment in support of a mixed-use development at Trademark House, Petersfield. The site was located in close proximity to a petrol filling station (PFS) and associated retail unit, which may result in loss of amenity at the development site. A two stage

Odour Assessment was undertaken to assess baseline conditions across the site and consider the risk of reduced amenity. Results of the assessment indicated odour effects at the site did not represent a constraint to planning consent. An Air Quality Benzene Assessment was also undertaken to determine potential exposure of future occupants to elevated benzene concentrations associated with the PFS. Results indicated that exceedences of the Air Quality Objective (AQO) were not predicted at the development location.

Granby Road, Buxton

Air Quality Assessment in support of a residential development on land off Granby Road, Buxton. Results of detailed dispersion modelling utilising advanced canyons indicated air quality impacts associated with the development were not significant. The scheme was also located in close proximity to Ashwood Dale Quarry. Potential impacts on future residential amenity were assessed using the Source-Pathway-Receptor approach, which indicated that existing emissions associated with the operation of the quarry were not considered significant.

Princess Road, Urmston

Odour Assessment in support of a residential development on Princess Road, Urmston. The site was located in close proximity to several fast-food takeaways which have the potential to cause odour emissions during normal operation. A mitigation scheme was therefore identified to protect future residents from loss of amenity. Subject to the inclusion of the specified mitigation, overall effects of odour were considered to be not significant at the development.

KEY EXPERIENCE:

Emily is a Principal Environmental Consultant with specialist experience in the air quality sector. Her key capabilities include:

- Production of Air Quality Assessments in accordance with Department for Environment, Food and Rural Affairs (DEFRA) methodologies for a range of residential, commercial and industrial sectors.
- Detailed dispersion modelling of road vehicle and industrial emissions using ADMS-Roads and ADMS-5. Studies have included impact assessment of ground level pollutant and odour concentrations and assessment of suitability of development sites for proposed end-use.
- Project management and co-ordination of Environmental Impact Assessments and scoping reports for developments throughout the UK.
- Assessment of fugitive dust impacts from a range of mineral extraction developments.
- Assessment of petrol stations to address benzene concentrations and their impact on adjacent developments.
- Production of air quality mitigation strategies specifically tailored to address issues at individual sites.
- Assessment of potential effects associated with network realignment schemes and highway developments.

SELECT PROJECTS SUMMARY:

Broad Street, Birmingham

Air Quality Assessment in support of a residential-led development on land at Broad Street, Birmingham. The proposals were located adjacent to a section of the Midland Metro Westside which runs along Broad Street. Consideration was made to the potential for re-alignment of the local road network as a result of the Metro to effect pollution levels at the development. The assessment indicated NO₂ concentrations exceeded air quality criteria from ground to third floor level as a result of road vehicle exhaust emissions. Mitigation was therefore specified for the affected units.

Home Farm, Forest Road, Warfield

Ecological Air Quality Assessment in support of a residential development. Natural England held concerns regarding potential impacts at sensitive ecological designations as a result of traffic exhaust emissions associated with the development. The predicted change in NO_x and ammonia concentrations and nitrogen and acid deposition was below the relevant criteria at all locations within the ecological designations. Impacts were therefore not considered to be significant.

Saltcoats Road, Stevenston

Air Quality Assessment in support of an educational campus and associated energy centre. Impacts associated with emissions from the proposed gas and biomass boilers were assessed through detailed dispersion modelling. This indicated impacts on annual mean NO₂ and PM₁₀ concentrations were predicted to be not significant.

Blackthorn & Piddington

Environmental Impact Assessment in support of a railway embankment scheme on land at the Network Railway Embankment between Piddington and Blackthorn. Due to the extensive stabilisation works a Fugitive Dust Emissions Assessment was undertaken in addition to consideration of road vehicle exhaust emissions. Due to the location of the site in relation to nearby sensitive receptors, potential impacts associated with construction works were not considered to be significant.

Blackmoorfoot Road, Huddersfield

Air Quality in support of a residential-led development in close proximity to an operational minerals facility. Due to the presence of the Johnsons Wellfield Quarry to the south of the site a Fugitive Dust Emissions Assessment was undertaken to determine potential impacts. Dispersion modelling of road vehicle exhaust emissions was also undertaken in support of the scheme. Results indicated the overall significance of fugitive dust emissions from the quarry and air quality impacts associated with operation of the development itself were not significant.

Lockwood Bar, Huddersfield

Air Quality Assessment for the proposed highway realignment scheme along Lockwood Road, Huddersfield. Changes in pollution levels were considered at sensitive receptors as a result of variations to road geometry and associated redistribution of vehicle trips across the local area. Results of the dispersion modelling study indicated air quality impacts as a result of the scheme were not significant.

MÜLLER