

Energy Statement

Ref: Z59554

**Proposed 20No. New Build
Dwellings**

at

Brookes Street, Middleton

for

Kwick Build Ltd



Energy Counsel
Viridor House
No.3 Bolholt Terrace
Bury/Gtr Manchester

BL8 1PP
Tel: +44 (0)161-762 1055
Fax: +44 (0)161-761 1094

Matthew.Gibson@energycounsel.co.uk
www.energycounsel.co.uk

Document Status – Final

Ref: Z59554			Date
Produced by:		Gideon Griffiths (OCDEA)	20 th September 2023
Checked by:		Matthew Adams BEng (Hons) LCEA level 5	20 th September 2023
Approved by:		Matthew Gibson BEng (Hons) CEng CEnv MIET MEI SocEnv	20 th September 2023

Disclaimer

This report has been prepared by Energy Counsel with all reasonable skill, care, and diligence within the terms of the Contract with the client, incorporating our Standard Terms and Conditions of Business and taking into account the resources devoted to it by agreement with the Client.

We disclaim any responsibility to the client and others in respect of any matters outside the scope of the above.

This report is confidential to the client, and we accept no responsibility of whatsoever nature to third parties to whom this report, or any part thereof, is made known. Any such party relies on the report at their own discretion and risk.

Contents

1. Introduction	6
1.1. Location.....	7
2. Policy Drivers for Energy Efficiency and Renewable Energy	10
2.1. National Policy	10
2.2. Local Policy	11
3. Methodology.....	12
4. Baseline Energy Assessment	14
4.1. Predicted Baseline Energy Requirements	15
5. Passive Design and Energy Efficiency.....	16
5.1. Passive Design Measures	16
5.2. Energy Efficient Systems.....	16
6. District & Communal Heating Networks	17
6.1. Decentralised Heating Networks.....	17
6.2. New Heating Networks – Options	18
7. Renewable Energy Technologies	19
7.1. Photovoltaics (PV).....	19
7.2. Solar Thermal HW Panels	20
7.3. Ground Source Heat Pump (GSHP)	21
7.4. Air Source Heat Pump/Exhaust Air Heat Pump	22
7.5. Micro Wind Power	22
7.6. Biomass	23
8. Energy Assessment of Proposed Scheme.....	25
9. Conclusion.....	27
9.1. Low/ Zero Carbon Technologies (LZT) Chosen.....	27
9.3. Summary Headlines	29
10. Appendices.....	30
10.1. LZT Feasibility Table	30
10.2. Specification for Energy Assessments (ADL1 2021 – SAP 10)	31
10.3. Index of Tables and Figures	33

Executive Summary

This Energy Statement has been developed in support of the planning application for the proposed development of 20No. residential dwellings at Brookes Street, Middleton. The statement will evaluate the technical and economic feasibility of using both passive and low and zero carbon technologies and will assess the practical levels of CO₂ reduction possible for this development to comply with the following planning requirements:

- National Planning Policy Framework (2021)
- Rochdale Core Strategy (2016)

The following low and zero carbon technologies have been evaluated:

- | | |
|--|-------------------------------|
| • Biomass | • Geothermal |
| • Wind | • Combined Heat & Power (CHP) |
| • Biogas | • Solar Hot Water |
| • Air Source Heat Pumps & Exhaust Air Heat Pumps | • Solar Photovoltaic |


The approach for the Brookes Street residential development is to embed sustainability into the heart of the development through a range of design measures based on the 'Be Lean, Be Clean, Be Green' design hierarchy. Measures will include:

1. Enhanced building fabric to meet the new Building Regulations ADL1 2021 (15/06/2022)
2. Enhanced air tightness and thermal bridging
3. Efficient continuous extract ventilation system using System 3 MEV
4. Heating and hot water will be provided by highly efficient air source heat pumps
5. Efficient lighting strategy primarily using LED type fittings

For the purpose of the assessment, we have evaluated a selection of dwelling types in SAP 10 (Standard Assessment Procedure) to provide an accurate estimate of predicted energy/CO₂ emissions. We have completed SAP calculations on the r dwelling to provide an accurate assessment of the total energy/emissions on site.

Summary

The development has been provided with energy savings through the use of passive improvement measures such as improved energy efficiency. This passive approach to compliance will complement the integrated approach to the sustainable energy objectives of the national and local policies. The use of heat pumps for heating and hot water in the dwellings achieves the necessary levels of carbon reduction.



The principles of a Be Lean, Be Clean, Be Green philosophy have been applied, resulting in a **60.23%** carbon emissions improvement and a **19.69%** primary energy improvement over Building Regulations Part L1 2021, as indicated in Table 1. A full design specification that confirms inputs used within the SAP calculations is provided within the appendices of this report.

Table 1 - Proposed development CO₂ emissions against Building Regulations Part L1 2021

	Total CO₂ Emissions (kgCO₂/yr)	Total Primary Energy (kWh/yr)
Target Dwelling Performance	19,129	78,700
Proposed Dwelling Performance	7,621	52,336
Total Reduction	11,508	26,364
Percentage Improvement (above ADL1 2021)	60.23%	19.69%

A fabric-first approach to meeting the Rochdale Core Strategy has been undertaken for the Brookes Street residential development, defined within the 'Be Lean, Be Clean, Be Green' energy hierarchy. The proposed design provides compliance with Building Regulations ADL1 2021, and with the application of heat pumps for heating and hot water ensures reductions which exceed the Rochdale Core Strategy requirements.

1. Introduction

The proposed development consists of 20No. 2 storey residential dwellings located at Brookes Street, Middleton. The development is required to achieve compliance under Building Regulations Approved Document Part L1 (2021) and meet Rochdale Core Strategy.

Supporting information is provided within this report for the proposed energy strategy to be considered on site in accordance with the following planning policies:

- Rochdale Core Strategy (2016)
- National Planning Policy Framework (2021)

Throughout this report, passive design techniques, energy efficient equipment and appropriate low carbon technologies will be appraised in line with the 'Be Lean, Be Clean, Be Green' philosophy of relevant planning documents and the Energy Hierarchy.

An assessment of CO₂ emissions will be made based on the calculation methodology dictated by the Standard Assessment Procedure (SAP) and in line with the requirements of Rochdale planning policy.

1.1. Location

The proposed development Brookes Street, in Middleton is highlighted by the red line boundary shown in Figure 1.



Figure 1 - Location of proposed Brookes Street residential development

The site will be accessed off Brookes Street, Middleton. Existing residential development exists on two sides of the development. The site is a typical suburban site.



Figure 2 – Site plan for the proposed Brookes Street residential development

The proposed development consists of 20No. dwellings, as indicated in Figure 2 above. Plot types and numbers are defined across the site as shown below:

Dwelling Type	Description	Number of Units
Type 1 – 2Bed House	2 Bed 4 Person Semi Detached House	11
Type 2 – 3Bed House	3 Bed 5 Person Semi Detached House	8
Type 3 – 3Bed House	3 Bed 5 Person Semi Detached House (CAT 3)	1
		20

Floor Plans

There are three house types as shown below:



Figure 3 House Types – 2B & 3B Houses

2. Policy Drivers for Energy Efficiency and Renewable Energy

This section presents a range of planning policy that is applicable to the Kenyon Lane residential development, at both a national and a local level.

2.1. National Policy

The National Planning Policy Framework was published in September 2023 and sets out the government's planning policies for England and they should be applied. Table 2 sets out the relevant energy standards for new developments and provides an indication of the design response to be provided.

Table 2 – Key National Planning Policy Requirements and Design Responses

Section	Policy Requirements	Design Response
14. Meeting the challenge of climate change, flooding and coastal change	The planning system should support the transition to a low carbon future in a changing climate, taking full account of flood risk and coastal change. It should help to: Shape places in ways that contribute to radical reductions in greenhouse gas emissions, minimise vulnerability and improve resilience; encourage the reuse of existing resources, including the conversion of existing buildings; and support renewable and low carbon energy and associated infrastructure.	This development will follow the principles set out in Rochdale Core Strategy (2016) using a 'Be Lean, Be Clean, Be Green' approach in reducing operational carbon emissions. An overview of current decentralised energy schemes in Manchester and an assessment on the potential for future schemes in relation to this development is provided in Section 6 of this report. This sustainability and renewable energy statement appraises site specific information to determine the most appropriate approach to minimise energy consumption.

2.2. Local Policy

The Adopted Rochdale Core Strategy (2016) provides a set of guidelines for new development within the local area. All relevant energy policy within these documents is provided within this section together with a design response.

Table 3 – Key Local Planning Policy Requirements and Design Responses

Rochdale Core Strategy (2016)		
Section	Policy Requirements	Design Response
G2 – Energy and New Development	All new development will be expected to adhere to the following energy hierarchy to the extent that policy G2 reflects national policy, targets and requirements for that type of development: 1. Demand Reduction – Achieve the maximum possible reduction in demand for energy through building design (i.e. the use of passive systems). At the design stage of new developments, every effort should be made to ensure that buildings use as little energy as possible throughout their lifetimes, using siting, orientation, layout, construction and landscaping to optimise use of natural passive systems such as solar gain and natural lighting, shading, ventilation and cooling to minimise heating, cooling and lighting demands. Green roofs and green walls should be incorporated into developments wherever feasible. 2. Energy efficiency and low / zero carbon technologies and networks – Design to maximize energy efficiency and use on-site or linked low or zero carbon technologies or direct connection to a low or zero carbon heat source (not necessarily on-site). 3. ‘Allowable solutions’ – use wider energy efficiency / CO₂ reduction measures, which could include developer contributions, to compensate for ‘residual emissions’ not addressed by 1 or 2 above.	The proposed development will follow the principles of the Energy Hierarchy by adopting a passive fabric-first approach to design and adopting the use of renewable technologies. The servicing strategy consists of an energy efficient air source heat pump system to provide low carbon heating and hot water to the dwellings with a coefficient of performance of >300+%. Enhanced thermal fabric and low air leakage is proposed to ensure the energy demand is reduced before considering any low/zero carbon technologies. The proposed development aims to look attractive whilst keeping the local identity and character of the area. An overview of current decentralised energy schemes in Rochdale and an assessment on the potential for future schemes in relation to this development is provided in Section 6 of this report.

3. Methodology

The first step of the full energy strategy assessment has been to undertake a baseline energy assessment. The baseline energy assessment consists of calculating the total CO₂ emissions of the development to meet Building Regulations and then compare the proposed improvement measures against this baseline. Building Regulations Part L1 2021 (SAP) applies to each of the 20No. dwellings and provides carbon emissions from regulated energy.

The building can then be benchmarked/thermally modelled using the energy hierarchy:

1. Be Lean <i>A reduction in energy use as a result of passive design and energy efficiency</i>
Thermal performance of envelope (U values) Glazing design Airtight construction Efficient mechanical ventilation Variable speed fans and pumps Efficient lighting
2. Be Clean <i>A focus on supplying energy to the development through efficient means</i>
Connect to low carbon heat networks Develop site wide heat network from single energy centre On site district heating network Provide energy efficient individual heating
• Be Green <i>The installation of renewable technologies to meet energy demand where possible</i>
Consider the feasibility of renewable energy technologies Assess the integration of renewable technologies based on the above measures

The development must be provided with energy savings through the use of thermal improvements to fabric (a 'fabric first' approach), followed by other clean energy solutions (energy efficiency improvements, district heating, etc...) and finally the use of renewable energy technologies, where

practical. This hierarchy complements the integrated approach to the sustainable energy objectives of Rochdale Core Strategy Planning Policies.

The planning policies require a full review of the technical and economic feasibility of the following renewable technologies:

- Biomass heating
- Biomass combined heat and power
- Solar hot water
- Solar photovoltaic
- Ground source heat pumps
- Air source heat pumps / exhaust air heat pumps
- Wind power

To achieve the targets set the development must achieve a balance between fabric, heating and control, ventilation and air leakage improvements, the amount of zero or low carbon technology installed and the capital, life cycle and running costs, maintenance, and operation, etc...

Feasible renewable energy technologies have been considered during the assessment to ensure the most suitable renewable energy is chosen for the demands of this scheme. The pros and cons of each technology with respect to this site are considered as part of this statement.

4. Baseline Energy Assessment

Energy Counsel have based the analysis on current Building Regulations ADL1 2021 (SAP 10), taking into account solutions that must not only be energy efficient but also practical, reliable and user friendly. Energy Counsel have carried out preliminary SAP 10 calculations for the dwellings. Under Building Regulations Part L1 2021, dwellings must comply with all three metrics set by the notional building shown below.

- Dwelling Emissions Rate (DER) must be lower than or equal to the Target Emissions Rate (TER)
- Dwelling Primary Energy Rate (DPER) must be lower than or equal to the Target Primary Energy Rate (TPER)
- Dwelling Fabric Energy Efficiency Rate (DFEE) must be lower or equal to the Target Fabric Energy Efficiency Rate (TFEE)

SAP 10 is the Governments Standard Assessment Procedure (SAP) for calculating the energy aspects of a dwelling. SAP is a measure of fuel costs for heating, hot water and lighting for a dwelling. SAP 10 can also be used to ascertain the energy requirements of a development.

To assess the baseline carbon emissions, we must make an estimation of the energy demands through Building Regulations in order to set a target upon which the actual development can be compared.

4.1. Predicted Baseline Energy Requirements

The predicted baseline CO₂ emission and primary energy demands for the development:

Table 4 - Baseline dwelling carbon emissions and primary energy

Our Ref	Dwelling Type	TER (Kg CO ₂ /yr/m ²)	TPER (kWh/yr/m ²)	Total Target Carbon Emissions (Kg CO ₂ /yr)	Total Target Primary Energy (kWh/yr)
Z59554	3B5P CAT 3	10.15	52.93	1,191	4,662
Z59555	2B4P	13.76	72.16	935	3,898
Z59556	2B4P	13.76	72.16	935	3,898
Z59557	2B4P	13.76	72.16	935	3,898
Z59558	3B5P	12.19	63.68	977	3,995
Z59559	3B5P	12.19	63.68	977	3,995
Z59560	3B5P	12.19	63.68	977	3,995
Z59561	3B5P	12.19	63.68	977	3,995
Z59562	2B4P	13.79	72.35	937	3,910
Z59563	2B4P	13.70	71.86	931	3,881
Z59564	3B5P	12.19	63.68	977	3,995
Z59565	3B5P	12.19	63.68	977	3,995
Z59566	3B5P	12.19	63.68	977	3,995
Z59567	3B5P	12.19	63.68	977	3,995
Z59568	2B4P	13.34	69.92	906	3,764
Z59569	2B4P	13.34	69.92	906	3,764
Z59570	2B4P	13.34	69.92	906	3,764
Z59571	2B4P	13.34	69.92	906	3,764
Z59572	2B4P	13.34	69.92	906	3,764
Z59573	2B4P	13.34	69.92	906	3,764
Total		256.48	1342.58	19,129	78,700

The baseline carbon emissions rate for the development is **19,129 KgCO₂/yr** and the baseline primary energy rate is **78,700 kWh/yr**.

5. Passive Design and Energy Efficiency

The approach of the development is to embed sustainability into the heart of the design from the outset of the project design process. The design will be developed with sustainable solutions, taking into account the relevant policies and strategies of Manchester City Council. The development will seek to consider all aspects and principles of sustainable development, taking into account environmental, social and economic impacts.

5.1. Passive Design Measures

The philosophy for the site is to achieve as much of the necessary reduction in carbon emissions through the use of passive design techniques and energy efficient measures as possible, before resorting to the use of LZCs. This ensures that the highest standards of building fabric and energy efficiency are achieved, rather than offsetting a poorer performance with LZC contributions.

This will be undertaken through a fabric first energy efficient design approach with high levels of thermal efficiency and a reduction in energy demand through efficient lighting design.

5.2. Energy Efficient Systems

Options have been reviewed for improving the energy efficiency of the development by installing an efficient hot water and heating system. The dwellings will benefit from high efficiency air source heat pump to deliver heating and hot water.

Dwellings will also be provided with a metering scheme based on their electricity usage.

A low energy high efficiency system 3 mechanical extract system will serve the kitchen and bathroom areas, with an overall specific fan power (SFP) of 0.18W/l/s per fan, in line with the requirements of Building Regulations Part F (2021). This system operates constantly on low extract and provides a boost when the wet room is in use. Ventilation will be provided throughout the rest of the dwelling by openable windows in all other spaces.

6. District & Communal Heating Networks

This section outlines how consideration of energy supplied efficiently from a district heating network can be provided to the dwellings in line with the energy hierarchy.

6.1. Decentralised Heating Networks

The energy policy reaffirms the view that energy generated by centralised power stations and transmitted through the national grid is highly inefficient and wasteful.

One of priorities for reducing CO₂ emissions is to reduce the reliance on centralised power stations. This means increasing the use of local, low-carbon energy supplies through de-centralised energy systems.

Decentralised plant generally means any heating and hot water and/or electricity generation provided on a district wide (DHN) or site wide (CHN) basis. DHN and CHN can typically include combined heat and power equipment (CHP). CHP is an engine which, when running, generates electricity and heats water which can then be distributed around a development.

A number of heat network opportunities across the region are at various stages of development. Benefits of district heating networks can include:

- Provision of low carbon / lower cost heat to domestic and commercial customers
- Diversification of the energy mix
- Reductions in region-wide carbon emissions
- Targeting and reduction of fuel poverty
- Potential long-term revenue streams for local authorities
- Alignment with regeneration programmes
- Driving the growth of the low carbon services sector

There are currently no existing district heating networks within proximity to the site.

6.2. New Heating Networks – Options

Consideration has been given to adopting a centralised or decentralised energy strategy. A decentralised energy option would typically be an energy centre distributing heat, hot water and electricity to the development from a single source either as a DHN or CHN. This typically would include boilers and a CHP type unit or district heat pumps, sized to provide the whole development. Sometimes multiple energy centres are used to split the loads, provide resilience and to serve different buildings.

The proposed heating and hot water demand from the development of 20No. dwellings is not sufficient to justify a DHN or CHN. The existing site is spatially constrained, there is insufficient space to locate the equipment and associated plant, and connection to a DHN would be cost prohibitive.

7. Renewable Energy Technologies

Energy Counsel have reviewed options for the use of on-site renewable energy/ Low or Zero Carbon Technology (LZT) in line with Manchester City Council policy aspirations.

This renewable energy statement/strategy reviews the technical and economic feasibility of the following technologies –

- Solar Photovoltaic
- Solar Hot Water
- Ground Source Heat Pumps
- Air Source Heat Pumps / Exhaust Air Heat Pumps
- Micro Wind Power
- Biomass

7.1. Photovoltaics (PV)

Photovoltaic panels convert sunlight into electricity to run lights and appliances. Photovoltaic panels use cells to convert light into electricity. A PV cell normally consists of 1 or 2 layers of a semi conducting material such as silicon. When light shines on a cell it generates energy causing electricity to flow, the higher the light intensity is, the more electricity flows.

The amount of energy PV cells generate is referred to as Kilowatt Peak (KWp). PV arrays now come in a variety of shapes and colours, ranging from grey 'solar tiles' that look like roof

tiles to panels and transparent cells that you can use on conservatories and glass to provide shading as well as generating electricity. The roof must be strong enough to take the weight of the panels, especially if the panel is placed on top of existing tiles. For flat roofs the panels can be mounted on A-frames to give the optimum angle.

The optimum panel inclination for solar collection is 35°, oriented due south; however panels that are inclined between 35° and 45° and oriented south of west or east are generally suitable. If solar




Figure 4 - Performance of photovoltaic panel orientation

collectors are oriented away from due south then a larger surface area will be required to generate a set amount of energy. The effect of non-optimal orientation is illustrated by the graph to the right:

The cost to install PV is typically £1,500 – 2,000 per kWp for 'on-roof' panel systems.

Although photovoltaic panels are a viable option they have not been proposed on these dwellings. Reasons are set out in Section 9.1.



Figure 5 - Photovoltaic array on a pitched roof

7.2. Solar Thermal HW Panels

Solar panel heating uses the radiant energy from the sun to heat hot water, most commonly for domestic hot water needs. There are two types of collectors used for solar water heating – flat plate collectors and evacuated tubes collectors. The systems function successfully in all parts of the UK, as they can work in diffuse light conditions. The collector should be mounted on a 10-60 degrees pitch facing south, although other variations can be used, south is the most efficient.

The cost of installing the system is dependent on the distance between the solar collector and the hot water storage and therefore costs vary. The closer the collectors are to the hot water storage; the less pipe work is required. Annual maintenance checks are recommended. The solar collectors are connected to a condensing boiler via a HW cylinder with twin coil.

A typical installation in the UK has a panel size of 3-5m² which is used in conjunction with a HW storage tank of 180-300litres, of which a minimum of 90-150 litres must be dedicated to solar hot water storage.




Figure 6 - The principles of a solar thermal system

They are a 'simple' and guaranteed technology which will act as a pre-heat for the Hot Water and Heating usage. Payback between capital cost and energy saving can normally be achieved within 12 – 20 years, subject to usage and dwelling type.

The use of solar thermal panels are applied best in conjunction with individual heating systems for each dwelling. The orientation of the development is fine for the utilisation of solar water heating to provide domestic hot water however it will not achieve significant carbon savings. Carbon savings of approximately 4-5% are achievable with this technology. The dwellings are unlikely to require sufficient hot water storage to deem solar thermal a feasible technology for this site. For the reasons aforementioned we do not consider this a viable option for this scheme.

7.3. Ground Source Heat Pump (GSHP)

GSHPs have been developed specifically for the housing market and are now considered to be an established reliable technology. The GSHP would be sized to cater for the heating and domestic hot water requirements. Typically, they are more suited to apartments as a centralised system would be installed with multiple bore holes to a depth of up to 125 metres depending on the ground conditions. GSHPs use a heat exchanger to extract heat from the earth.

The efficiency of ground source heat pumps is measured by Co-efficient of Performance (CoP), this is




Figure 7 - Principles of a GSHP system

the ratio of units of heat output for each unit of electricity used to drive the compressor and pump for the ground loop. Average CoP is around 2-4 although some systems may produce a greater rate of efficiency. This means that for every unit of electricity used to pump the heat, 2-4 units of heat are produced, making it an efficient way of heating a building. If grid electricity is used for the compressor and pump, then there is the opportunity to consider a

range of energy suppliers to benefit from the lowest running costs, for example by choosing an economy 10 or economy 7 tariff.

Due to the scale of these dwelling units, GSHPs are not considered an appropriate design solution.

7.4. Air Source Heat Pump/Exhaust Air Heat Pump

Air source heat pumps (ASHP) and exhaust air heat pumps (EAHP) work in a similar way to GSHP. Air source heat pumps can be fitted on the external façade or in the roof space. An air source heat pump uses small amounts of electricity to take in large quantities of air and extract heat. The efficiency of ASHP is measured by Coefficient of Performance (CoP); this is the ratio of units of heat output for each unit of electricity used to drive the system. Average CoP is around 2-4 although some systems may produce a greater rate of efficiency.




Figure 8 - Principles of an ASHP system

Exhaust air heat pumps such as the NIBE F370 work in a similar manner to ASHP units but have only indoor units (no outdoor compressors) and in addition they also recover heat from their integral exhaust air ventilation system. These units work well on apartment blocks and dwellings where mains gas is unavailable or unsuitable for a development. They are expensive in terms of capital cost of the equipment, installation and the enhanced structural requirements.

Air Source Heat Pumps are considered the most appropriate technology for this scheme and can be utilised to deliver efficient heating and hot water throughout the dwellings. The introduction of this technology ensures that carbon emissions reductions can be provided in line with Rochdale Core Strategy (2016).

7.5. Micro Wind Power

Wind power is one of the cleanest and safest methods of generating electricity. However, wind power is unfeasible due to the fact the development is in an urban area and local wind conditions would not be sufficient to provide enough power. Most small wind turbines generate Direct Current (DC) electricity. Systems that are not connected to the national grid require battery storage and an inverter to convert DC electricity into Alternating Current (AC) which is mains electricity.

There are two types of wind turbine available:

- Roof mounted – These are mounted on the roof of dwellings
- Mast mounted – Which are free standing

Important issues to consider when using wind turbines are:

- Wind speed increases with height so it's best to have the turbine high on a mast or tower.
- The ideal site is a smooth top hill with a flat, clear exposure, free from excessive turbulence and obstructions such as large trees, dwellings or other buildings.
- Small scale wind power is particularly suitable for remote off grid locations where conventional methods of supply are expensive or impractical.
- Where the local annual average wind speed is 6 m/s or more.
- Where there are no significant nearby obstacles such as buildings, trees or hills that are likely to reduce the wind speed or increase turbulence



Figure 9 - Mounted wind turbine

As this development is in an urban area there will be obstacles which reduce wind speed. The average wind speed in this area is 4.7 m/s at a height of 10 metres, which is less than the 6 m/s required. Therefore, micro wind is not a viable technology for this development. Please refer to section 9.1 for more details.

7.6. Biomass

Biomass is a generic name for any fuel produced from organic sources and falls into mainly two categories:

- Woody biomass- forest products, untreated wood products, energy crops and wood pellets
- Non-wood biomass – liquid biofuels (such as biodiesel, bioethanol) or animal waste industrial municipal products and high energy crops such as rape seed, sugar cane and maize.

For domestic properties the fuel used is normally wood pellets, wood chips or wood logs. For larger applications, biomass boilers replace conventional fossil fuel boilers and come with an automated feed by screw drives from hoppers.

Biomass systems require more cleaning than gas or oil boilers and they must be capable of being taken out of service for cooling and cleaning whilst maintaining the building heating supply particularly in

communal heating systems. Centralised gas boilers are therefore still required to support the biomass boiler, which would be the lead boiler. The size of the dedicated plant rooms is substantial. Fuel availability, delivery and storage are also important issues to consider.

Air quality issues are also an important factor when looking to install biomass. The cost of the fuel depends on the type, delivery distances and whether it is obtained as simple waste product or from another organisation. The cost of wood pellets is currently a little more expensive than mains gas, and woodchip is approx. 30% cheaper, however prices are fluctuating rapidly in the bio-fuel market at the present time creating uncertainty over their take up.



Figure 10 - Biomass boiler and hopper

Biomass CHP is still relatively new to the UK market and is more suitable to large developments where energy demand does not require significant modulation. There are technical issues with small scale Biomass CHP and until these can be resolved and proven the take up of these systems in the UK and Europe has been slow.

Overall carbon savings of 40%+ are achievable with biomass technology. Biomass is more suited to a communal heating system; there is insufficient space to accommodate the equipment and fuel storage to facilitate a biomass boiler. Furthermore, there are noise and air quality issues associated with this type of technology. For these reasons, biomass is discounted.

8. Energy Assessment of Proposed Scheme

The Brookes Street residential development has adopted the principles of the 'Be Lean, Be Clean, Be Green' approach. The most practical and economically feasible solution for the development is a good quality thermally insulated fabric, air-tight envelope, passive improvements and the use of highly efficient heat pumps supported by efficient ventilation extract system.

Table 5 - Proposed carbon emissions from Brookes Street residential development

Our Ref	Dwelling Type	DER	TER	%	DPER	TPER	%	Total Target Carbon Emissions (Kg CO ₂ /yr)	Total Target Primary Energy (kWh/yr)
Z59554	3B5P CAT 3	4.28	10.15	57.83	44.94	52.93	15.09	502	3,418
Z59555	2B4P	5.23	13.76	61.99	55.35	72.16	23.29	355	2,446
Z59556	2B4P	5.23	13.76	61.99	55.35	72.16	23.29	355	2,446
Z59557	2B4P	5.31	13.76	61.41	56.21	72.16	22.1	361	2,484
Z59558	3B5P	4.99	12.19	59.06	52.69	63.68	17.26	400	2,747
Z59559	3B5P	4.99	12.19	59.06	52.69	63.68	17.26	400	2,747
Z59560	3B5P	4.99	12.19	59.06	52.69	63.68	17.26	400	2,747
Z59561	3B5P	4.99	12.19	59.06	52.69	63.68	17.26	400	2,747
Z59562	2B4P	5.33	13.79	61.35	56.37	72.35	22.09	362	2,491
Z59563	2B4P	5.31	13.70	61.24	56.14	71.86	21.87	360	2,481
Z59564	3B5P	4.99	12.19	59.06	52.69	63.68	17.26	400	2,747
Z59565	3B5P	4.99	12.19	59.06	52.69	63.68	17.26	400	2,747
Z59566	3B5P	4.99	12.19	59.06	52.69	63.68	17.26	400	2,747
Z59567	3B5P	4.99	12.19	59.06	52.69	63.68	17.26	400	2,747
Z59568	2B4P	5.21	13.34	60.94	55.17	69.92	21.1	354	2,439
Z59569	2B4P	5.21	13.34	60.94	55.17	69.92	21.1	354	2,439
Z59570	2B4P	5.21	13.34	60.94	55.17	69.92	21.1	354	2,439
Z59571	2B4P	5.21	13.34	60.94	55.17	69.92	21.1	354	2,439
Z59572	2B4P	5.21	13.34	60.94	55.17	69.92	21.1	354	2,439
Z59573	2B4P	5.12	13.34	61.62	54.16	69.92	22.54	347	2,394
Total/Average		101.78	256.48	60.23	1075.89	1342.58	19.69	7,621	52,336

The predicted carbon emissions for the proposed development are **7,621 kgCO₂/yr**. This is a total carbon reduction of **11,508 kgCO₂/yr** from the baseline emissions of **19,129 kgCO₂/yr**. This equates to a **60.23%** carbon reduction.

The predicted primary energy rate for the proposed development is **52,336 kWh/yr**. This is a primary energy reduction of **26,364 kWh/yr** from the baseline primary energy rate of **78,700 kWh/yr**. This equates to an **19.69%** primary energy reduction.

The development proposal achieves carbon efficiency reductions through a highly efficient thermal fabric, energy efficient lighting and ventilation, improved thermal bridging, low air leakage and highly efficient heat pumps for heating and domestic hot water to reduce emissions in line with Rochdale Core Strategy.

9. Conclusion

Following the 'Be Lean, Be Clean, Be Green' hierarchy, the proposed design solutions on the Brookes Street development are predicted to:

- 1) Reduce the total carbon emissions by 60.23% compared to new Building Regulations ADL 2021. New Building Regulations are a 31% improvement on 2013 regulations, which in turn were a 6% improvement on 2010 regulations upon which the energy policies are based. Therefore the project significantly exceeds energy policy EN6 2010 regulations by 97.23%.
- 2) The heat pumps are the proposed renewables/ low carbon technology. Their contribution to the overall energy reduction under the 'be green' energy hierarchy is approx. 50%.
- 3) Reduce the total primary energy by 19.69% compared to new building regulations ADL 2021. This is a new metric under Part L 2021.

The approach for the Brookes Street residential development is to embed sustainability into the heart of the development through a range of design measures based on the 'Be Lean, Be Clean, Be Green' design hierarchy. Measures will include:

- 1) Enhanced building fabric to meet the new Building Regulation ADL1 2021 (15/06/2021)
- 2) Enhanced air tightness and thermal bridging
- 3) Efficient continuous extract ventilation system using System 3 MEV
- 4) Heating and hot water will be provided by highly efficient air source heat pumps
- 5) Efficient lighting strategy primarily using LED type fittings

9.1. Low/ Zero Carbon Technologies (LZT) Chosen

- Air source Heat Pumps (ASHP) are viable and are considered most suitable for this development for the following reasons:
 - a) The ASHP achieves a 50%+ reduction in CO2 emissions based on the SAP 10 ADL1 2021 standards.
 - b) Every dwelling benefits directly from the Heat pump performance.
 - c) Heat pumps require very little maintenance and have a long service life.

9.2. Low/ Zero Carbon Technologies (LZT) Discounted

- Solar Thermal Hot Water is viable however it is discounted for the following reasons:
 - a) The dwellings will have a HW cylinder but solar thermal is not proposed as the hot water is being supplied from an efficient air source heat pump.
 - b) CO₂ savings from this technology are not significant enough to justify the cost of these systems.
 - c) Increased maintenance and operating costs. These include annual service, heat transfer fluid changes and filter changes.
 - d) Access to the roof will require RAMS and is a high risk item.

- PV is viable option however it has been discounted for the following reasons:
 - a) A fabric first approach with efficient heat pump is the preferred solution in this instance and Photovoltaic solar panels have not been specified for this development.
 - b) CO₂ savings are beneficial and could be considered as a future retrofit solution to meet zero carbon.
 - c) Affordability issues related to CAPEX of PV.
 - d) Increased maintenance and operating costs. These including an annual service and cleaning – refer to access issues below.
 - e) Access to the roof will require RAMS and is high fire risk item with electric cabling passing through the dwelling.

- Biomass has been discounted for the following reasons:
 - a) It poses problems in terms of delivery of fuel.
 - b) It poses problems in terms of air quality issues.
 - c) Storage and transportation for deliveries would be required.
 - d) It would require a centralised larger plant space for storing fuel, which on this constrained site is not viable.

- Micro-wind has been discounted for the following reasons:
 - a) Turbines do not work on this type of development due to problems with wind turbulence and mounting of the units.
 - b) The wind speeds in the area are not conducive to wind power electricity generation and there would be issues with turbulence, wind shading, noise and air traffic.

- Ground Source Heat Pumps (GSHP) are not viable for site due to the following reasons:
 - a) The size of the development is very small for a GSHP system. Costs increase for smaller developments.
 - b) Ground conditions are unknown which is a large risk item.
 - c) Site spatial requirements are limited and unfeasible for vertical bore holes or horizontal slinky type units.

A more detailed overview of LZT technologies is provided in the appendices of this report.

9.3. Summary Headlines

- A fabric-first approach to meeting Rochdale Core Strategy has been undertaken for the Brookes Street residential development, defined within the 'Be Lean, Be Clean, Be Green' energy hierarchy. The proposed design provides compliance with Building Regulations ADL1 2021, and with the application of heat pumps for heating and hot water ensures reductions which exceed Rochdale Core Strategy.
- The use of high-efficiency heat pumps reduces carbon emissions by 60.23% and provides a primary energy reduction of 19.69% when compared to new Building Regulations Part L 2021.

An overall 60.23% improvement in CO₂ emissions and a 19.69% improvement in primary energy above the Building Regulations baseline is proposed to support our application. The project significantly exceeds energy policy EN6 2010 regulations by 97.23%.

	Total CO ₂ Emissions (kgCO ₂ /yr)	Total Primary Energy (kWh/yr)
Target Dwelling Performance	19,129	78,700
Proposed Dwelling Performance	7,621	52,336
Total Reduction	11,508	26,364
Percentage Improvement (above ADL1 2021)	60.23%	19.69%

10. Appendices

10.1. LZT Feasibility Table

Technology	Technical Feasibility	Carbon Savings	Estimated Costs	Financial Viability
Solar photovoltaics	A photovoltaic array is not required for the dwellings as carbon emissions reductions in line with BRegs Part L1 2021 are already achieved.	A 1kWp system could save around 213 kg of CO ₂ / year per dwelling	Average cost for such a system is around £1.5K per dwelling.	Current potential income generation is around £120 minimum per annum per dwelling with a fuel cost saving of around £40 / year per dwelling.
Wind	Average wind speeds on the site according to the <u>NOABL</u> Wind Speed Database are 4.7m/s. To be technically feasible a minimum of 6m/s is required, therefore this site is not considered feasible.	N/A	N/A	N/A
Micro Hydro	There is no capacity for micro hydro on this site since there are no local water courses available.	N/A	N/A	N/A
District Heating	There are no existing or planned district heating networks to facilitate connection at this stage.	N/A	N/A	N/A
Solar Hot Water	This technology has been discounted as the level of hot water usage in each dwelling does not merit a storage system, which poses space issues.	Around 270 kg of CO ₂ / year per dwelling.	£3-5K per dwelling	Income generation from RHI in a 4-person household would be in the region of £340 / year (per dwelling) with a fuel saving of around £65 / year per dwelling
Heat Pumps	GSHP: Ground conditions on site are unknown, and installation of coils are likely not economically viable for this project. ASHP: Provided to all dwellings for heating and hot water. HWHP: Provided to all dwellings for hot water	GSHP: 2,100 to 3,300 kg CO₂ / year per dwelling ASHP: 1,700 to 2,700 kg CO₂ / year per dwelling. HWHP: 1,700 to 2,700 kg CO₂ / year per dwelling.	GSHP @ £13-20K per dwelling ASHP: £7-11K / dwelling ASHP: £3K / dwelling	GSHP: £2,590 minimum annual RHI income generation per dwelling with fuel saving of £440 / year minimum per dwelling ASHP: RHI removed. Fixed £5000 grant fund per property. HWHP: N/A
Biomass	The small scale of this development would not facilitate the installation of biomass boilers due to the space required for pellet storage.	N/A	N/A	N/A

10.2. Specification for Energy Assessments (ADL1 2021 – SAP 10)

Item	Brief Description	Notes	Confirm
	The following information is required for the design submission (as per requirements of AD L1).	Please note submission is in two stages. A) Design , B) As installed	
1. Dwelling Type			
1.1	Building Regulations Part L1 2021 apply.		
1.2	Post code of site will be provided at a later date	Royal mail postcodes	
1.3	Electricity is supplied by standard tariff rather than economy 7, 10 or 24.	Assumed Standard tariff	
1.4	It is assumed that the dwellings have a Medium thermal mass parameter.	Timber construction	
2. Floor Construction Details			
2.1	Ground floor is insulated to achieve the U-value stated opposite. 150mm PIR insulation or equivalent	U-Value = 0.12W/m ² K	
3. Wall Construction Details			
3.1	Main external walls to achieve the U-value stated opposite.	U-Value = 0.18 W/m ² K	
4. Roof Construction Details			
4.1	Cold roofs are insulated to achieve the U-value indicated opposite. 500mm mineral wool quilt.	U-Value = 0.09 W/m ² K	
5. Openings			
5.1	External doors/Doors to cold corridors are installed to achieve the U-value stated opposite.	U-Value = 1.4 W/m ² K	
5.2	All double-glazed windows, rooflights and patio type doors/windows with Low-e glass hard coating to achieve the U-Value stated opposite.	U-value = 1.3 W/m ² K. G-value = 0.4 BFRC	
6. Ventilation			
6.1	Design stage SAP calculation presumes an air permeability of 4m ³ /m ² /hr at 50pa will be achieved.	5m ³ /m ² /hr at 50pa – 2B3P & 3B5P 4.5m ³ /m ² /hr at 50pa – 3B5P (CAT3)	
6.2	System 3 decentralised Mechanical extract ventilation is installed in wet areas.	Greenwood Unity CV3 or equal and approved	
6.3	No open flues or fireplaces or flue-less gas fires are present anywhere.		
7. Space Heating			
7.1	There is only one main heating system installed to all dwelling types.	No secondary heating.	
7.2	Heating is provided by air source heat pumps.	Daikin Altherma EDLA06EV3 used for calculation	
7.3	The heating system for the dwelling has time and temp zone control.		
8. Water Heating			
8.1	Hot Water is provided by an Air Source Heat Pump to a 200litre cylinder	200L pre-plumbed cylinder with heat loss of 1.4kwh\day	
8.2	Independent time control is provided to the hot water cylinder.		
8.3	All showers will be supplied from the hot water cylinder via a pump. All showers to be flow regulated to <8litres/minute.		
8.5	Water usage per person per day is ≤125 Litres.	To meet or exceed Part G. Requires good specification of flow rates on all water consuming appliances – taps, showers, etc	
9. Renewables			

9.1	The heat pump is considered a low carbon technology under the 'Be Green' Energy Hierarchy.		
10. Other			
10.1	The Contractor will be responsible for undertaking thermal bridging calculations for each detail to provide a comprehensive set of calculations to meet building regs compliance ADL1 2021. They will be responsible for meeting a overall Y value of 0.06W/mK (summations of all the junctions)	Y Value target 0.06W/mK	
10.2	Split lintels or insulated thermally broken lintels will be used throughout	Applicable for masonry construction	
10.3	Low energy (LE) lights are installed throughout.	All lighting must be specified with efficacy of 80 lumens/circuit watt or more.	
10.4	Dwellings will require further analysis under part O	Part O overheating assessment required for dwellings	

10.3. Index of Tables and Figures

Figure 1 - Location of proposed Kenyon Lane residential development	7
Figure 2 – Site plan for the proposed Kenyon Lane residential development	8
Figure 3 – Floor plans House Type 3 2B4P	Error! Bookmark not defined.
Figure 4 - Performance of photovoltaic panel orientation	Error! Bookmark not defined. 2
Figure 5 - Photovoltaic array on a pitched roof	Error! Bookmark not defined. 3
Figure 6 - The principles of a solar thermal system	Error! Bookmark not defined. 3
Figure 7 - Principles of a GSHP system.....	Error! Bookmark not defined. 4
Figure 8 - Principles of an ASHP system.....	Error! Bookmark not defined. 5
Figure 9 - Mounted wind turbine.....	Error! Bookmark not defined. 6
Figure 10 - Biomass boiler and hopper	Error! Bookmark not defined. 7
Table 1 - Proposed development CO ₂ emissions against Building Regulations Part L1 2021.....	5
Table 2 – Key National Planning Policy Requirements and Design Responses.....	10
Table 3 – Key Local Planning Policy Requirements and Design Responses	11
Table 4 - Baseline dwelling carbon emissions and primary energy	15
Table 5 - Proposed carbon emissions from Kenyon Lane residential development	25