



Category	Emergency
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail
Specification	Performance

Falcon Pro

Falcon Pro DALI Surface Mounted Downlight Black

Code: AFLP/1/B/3NM/DA



PRODUCT FEATURES

- Compact surface ultra-low profile recessed DALI emergency downlight
- High specification optic design and performance allows increased spacing providing reduced cost
- Self-test as standard
- Supplied with open area and escape route interchangeable lenses
- Available in black and white finishes
- BESA and side conduit mounting

GENERAL INFORMATION

Wattage	2W
Lumens Delivered	223lm(OA) 228lm(ER)
Lm/W	111lm/W
Beam Angle	Open area - 125° / Escape route - 75°/135°
CRI	Ra 70
CCT	6500K+/-500K
Input	220-240V
Operating Temp	5°C - 50°C
SDCM	6
Product Weight without Packaging	0.37 kg

TECHNICAL INFORMATION

Light Source	LED
Colour / Finish	Black
IP Rating	IP65
IK Rating	IK08
Class Protection	2
Internal / External	Internal / External
Surface / Recessed / Suspended	Ceiling
Lumen Depreciation	L80 59,000h
Warranty (Years)	7
CE Mark	Yes
Height	49 mm
Emergency Output Duration	3 Hr





Category	Emergency
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail
Specification	Performance

Falcon Pro

Falcon Pro DALI Surface Mounted Downlight Black

Code: AFLP/1/B/3NM/DA



SPARES

ASBP/29/LI

3.2v 3400mA Lithium

