



SURVEY SHEET		CUSTOMER		JOB DETAILS	
		AZAM TEL :		YOUR REF : OUR REF : 84 DATE : 07/05/2026 JOB SPEC : Glazed	
1 M70 Casement [Style 101 [1]] Qty : 1 4/18/6. Acoustic Lam/Soft Coat : 18mm Black S/Spacer Argon Gas Filled		Location : 		DIMENSIONS Width _____ Height _____ Transom _____ Mullion _____ Other Information _____	
		O/A Frame Size 900mm x 1125mm : Basic Frame Size 900mm x 1095mm :			
Accreditations	BS7412	Bead colour	White	Bead type	Sculptured Bead (New M70)
Cill	150mm Cill	Cill colour	White	Colour	White
Drainage	Concealed/Base	Frame (Cill)	101.309 67mm Frame	Frame (Head)	101.309 67mm Frame
Frame (Left jamb)	101.309 67mm Frame	Frame (Right jamb)	101.309 67mm Frame	Gasket	Black Gasket
Glazed in/out	Glazed in	Handle Type	Sweet Cranked (35mm) S	Reinforcing rule	Domestic Reinforcing
Reinforcing type	Per Supplier Specification	Ventilator (Head)	Link Vent 5000	W.E.R	No Energy Rating
2 M70 Casement [Style 202 [1]] Qty : 1 4/18/6. Acoustic Lam/Soft Coat : 18mm Black S/Spacer Argon Gas Filled		Location : 		DIMENSIONS Width _____ Height _____ Transom _____ Mullion _____ Other Information _____	
		O/A Frame Size 700mm x 1125mm : Basic Frame Size 700mm x 1095mm :			
Accreditations	BS7412	Bead colour	White	Bead type	Sculptured Bead (New M70)
Casement locking	Yale Shootbolt	Cill	150mm Cill	Cill colour	White
Colour	White	Drainage	Concealed/Base	Frame (Cill)	101.309 67mm Frame
Frame (Head)	101.309 67mm Frame	Frame (Left jamb)	101.309 67mm Frame	Frame (Right jamb)	101.309 67mm Frame
Friction stay	Defender Standard	Gasket	Black Gasket	Glazed in/out	Glazed in
Handle	White Handles Sweet Cran	Handle Type	Sweet Cranked (35mm) S	Hinge Protectors	No Hinge Protectors
Open in/out	Open out	Reinforcing rule	Domestic Reinforcing	Reinforcing type	Per Supplier Specification
Sash (Cill)	76mm Casement Sash	Sash (Head)	76mm Casement Sash	Sash (Left jamb)	76mm Casement Sash
Sash (Right jamb)	76mm Casement Sash	Sash colour	White	Ventilator (Sash)	Link Vent 2500 (Sash)
W.E.R	No Energy Rating				